

## Mechanical Time Switch - 24-Hour 120V Mechanical Time Switch, SPST, Pool Heater Protection, Type 3R Plastic Enclosure

Item T101P201



### PRODUCT DESCRIPTION

Heavy-duty mechanical time switches control a single load

### FEATURES

- Highest motor load ratings in the industry
- 12 ON/OFF operations per day
- One ON and one OFF tripper included
- Available with pool heater protection
- Teeter-type terminals for multiple load connections

### APPLICATIONS

- Heater Thermostat Control
- Motor Control
- Pump Control

### TECHNICAL DATA

#### General

Model Number	T101P201
Description	24-Hour 120V Mechanical Time Switch, SPST, Pool Heater Protection, Type 3R Plastic Enclosure
UPC Code	078275700574
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Maximum ON/OFF Operations	12
Operation Mode	24 hour
Application Compatibilities	LED

#### Mechanical Specifications

Enclosure Type	Outdoor type 3R plastic
----------------	-------------------------

#### Dimensions

Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Knockout Dimensions Bottom	(2) 1/2" and 3/4"
Knockout Dimensions Back	1/2" and 3/4" combination

#### Material Specifications

Color	Gray
-------	------

#### Load Ratings

Tungsten Range(s)	40 A, 120-480 VAC, 60 Hz
Electronic Ballast	16 A
Electronic Ballast Load Ratings Ranges	16 A, 120 VAC

Inductive	40 A @ Varying Voltages, 60 Hz; 40 A, 277 VAC, 60 Hz; 40 A, 240 VAC, 60 Hz; 40 A, 208 VAC, 60 Hz; 40 A, 120 VAC, 60 Hz
Resistive Load Ratings Ranges	40 A, 120-480 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120-480 VAC, 60 Hz
Pilot Duty Load Ratings Ranges	1000 VA, 120-480 VAC, 60 Hz
Motor Load Ratings Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz

#### Electrical Specifications

Heater Control Output	10 A, 250 VAC MAX, 60 Hz
Wiring Option	Terminals
Input Voltage Range(s)	120 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPST
Maximum Power Consumption (W)	3 W
Hz	60

#### Packaging

Shipping Weight (lbs)	2.345
Unit Carton Dimensions (H x W x L) in	4.25 x 7.31 x 11.75 in

#### Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

#### Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED; Green Energy
California Proposition 65	Lead
RoHS Certification	N/A

---

**ACCESSORIES**


156T1978AMX

1 Set of ON/OFF Trippers for T100,  
T7000, and WH40



156T1978A

Extra/replacement trippers 1 ON and 2 Insulator for Mechanical Time Switches Skipper Screws (3 per package)  
- 10 Pack



124T2411A

CAUTION - RISK OF ELECTRICAL SHOCK  
Turn power off at main panel before  
servicing this switch or the equipment it  
controls. Use only with 120VAC power only.  
Reinstall this insulator after wiring.



156T1957A



22T338GR

Mounting Bracket for Intermatic  
Standardized Timer Mechanisms



WG430-20D

MOTOR-BOXED, 125V 60HZ



6T1396

Cover, Beige plastic