

Plug-In Timer - 7-Day Outdoor Digital Plug-In Timer

Item HB880RMX



NOM

PRODUCT DESCRIPTION

Full feature plug-in timer provides 7-day programming in a weatherproof enclosure with astronomical clock and Daylight Saving Time (DST) adjustment in a convenient plug-in for quick and easy automation.

FEATURES

- ▶ 14 ON/OFF programmable events
- ▶ Full 7-day programming options, including astronomical clock, automatic DST adjustment and random mode
- ▶ 2 grounded receptacles with 24" cord and grounded plug
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ AA battery backup (included)
- ▶ Plugs directly into wall outlet

APPLICATIONS

- ▶ Landscape Water Control
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	HB880RMX
Description	7-Day Outdoor Digital Plug-In Timer
UPC Code	078275140134
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Maximum ON/OFF Operations	14
Operation Features	Astronomic
Operation Mode	7 day
Backup Type	Battery
Battery Type	AA
Battery Service Type	Replaceable
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Alkaline

Mechanical Specifications

Number of Plugs	2
Plug Configurations	5-15

Dimensions

Product Dimensions (H x W x D) in	5.375 x 5 x 1.875 in
-----------------------------------	----------------------

Material Specifications

Color Black

Load Ratings

Incandescent Load Ratings	1000 W, 120 VAC, 60 Hz
Electronic Ballast	500 VA, 120 VAC, 60 Hz
Inductive	8.3 A, 120 VAC, 60 Hz
Motor Load Ratings Ranges	1/2 HP, 120 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Hz	60

Packaging

Shipping Weight (lbs)	0.948
Unit Carton Dimensions (H x W x L) in	7 x 3 x 5.5 in

Environmental Specifications

Usage Environments	Outdoor
--------------------	---------

Standards and Certifications

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A