

## Electronic Timer Control - Electronic Pump Motor Controller with Seasonal Adjustment, 4-Circuit, Mechanism Only

Item P1403ME



### PRODUCT DESCRIPTION

Control single- and two-speed pumps and auxiliary equipment with this 3-circuit programmable device. The seasonal adjustment feature can be programmed to automatically adjust filter pump ON/OFF schedules according to the season.

### FEATURES

- Saves up to 40% in monthly utility bills compared to standard timers
- Meets most rebate incentives
- Enables separate daily schedules
- Easy-to-follow on-screen setup for programming
- Auto-voltage adjust
- Efficient low-speed operation for all seasons
- User programmable high and low-speed events
- 100+ hour supercapacitor memory retention
- Available with Type 3R indoor/outdoor lockable metal enclosure

### APPLICATIONS

- Motor Control
- Pump Control

### TECHNICAL DATA

#### General

Model Number	P1403ME
Description	Electronic Pump Motor Controller with Seasonal Adjustment, 4-Circuit, Mechanism Only
UPC Code	078275139947
Brand	Intermatic
Country of Origin (Intermatic)	CANADA
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	23 hours, 59 minutes
Maximum ON/OFF Operations	3
ON/OFF Operations	3
Daylight Savings Adjustment	Automatic
Backup Type	Supercapacitor

#### Material Specifications

Color	Black
-------	-------

#### Communication Method

Has WiFi	No
----------	----

#### Load Ratings

Tungsten Range(s)	5 A @ 120-277 VAC, 50/60 Hz
-------------------	-----------------------------

Inductive	30 A @ 24 VAC, 60 Hz; 30 A @ 24 VAC, 50 Hz; 120-277 VAC
Resistive Load Ratings Ranges	30 A @ 24 VAC, 120-277 VAC, 50/60 Hz; 20 A @ 28 VDC
Inductive Load Ratings Ranges	30 A @ 24 VAC, 120-277 VAC, 50/60 Hz
Motor Load Ratings Ranges	16 FLA, 96 LRA @ 120 VAC, 50/60 Hz; 17 FLA, 80 LRA @ 240 VAC, 50/60 Hz

**Electrical Specifications**

Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Number of Circuits	3
Switch Type	4-SPST
Maximum Power Consumption (W)	7 W
Hz	50/60

**Packaging**

Shipping Weight (lbs)	1.657
Unit Carton Dimensions (H x W x L) in	4.25 x 7.25 x 11.5 in

**Standards and Certifications**

CSA Certification	cCSAus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A