

Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Type 3R Plastic Enclosure

Item PE153P



PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

FEATURES

- Controls single- and two-speed pumps and cleaner/booster pumps
- Three ON/OFF events per circuit per day
- Seven preprogrammed modes
- Freeze and heater protection
- LCD readout
- Multi-voltage input and output
- Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

APPLICATIONS

- Motor Control
- Pump Control

TECHNICAL DATA

General

| | |
|--------------------------------|-----------------------------------------------------------------------|
| Model Number | PE153P |
| Description | 24-Hour Electronic Time Control, 3-Circuit, Type 3R Plastic Enclosure |
| UPC Code | 078275092396 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CANADA |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|---------------------------|---------|
| Maximum ON/OFF Operations | 3 |
| Operation Mode | 24 hour |

Mechanical Specifications

| | |
|----------------|-------------------------|
| Enclosure Type | Outdoor type 3R plastic |
|----------------|-------------------------|

Dimensions

| | |
|-----------------------------------|------------------------|
| Product Dimensions (H x W x D) in | 9.375 x 5.5 x 3.625 in |
|-----------------------------------|------------------------|

Material Specifications

| | |
|-------|-------|
| Color | Black |
|-------|-------|

Communication Method

| | |
|----------|----|
| Has WiFi | No |
|----------|----|

Load Ratings

| | |
|-------------------------------|-----------------------------|
| Tungsten Range(s) | 5 A, 120/240 VAC, 50/60 Hz |
| Resistive Load Ratings Ranges | 17 A, 120/240 VAC, 50/60 Hz |

Motor Load Ratings Ranges 80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz

Electrical Specifications

| | |
|------------------------|-----------------------|
| Voltage Selection Type | Multi-Voltage |
| Input Voltage Range(s) | 120/240 VAC, 50/60 Hz |
| Number of Circuits | 3 |
| Switch Type | 3-SPST |
| Hz | 50/60 |

Packaging

| | |
|---------------------------------------|---------------------------|
| Shipping Weight (lbs) | 2.595 |
| Unit Carton Dimensions (H x W x L) in | 4.251 x 7.251 x 11.751 in |

Standards and Certifications

| | |
|------------------------------------------|--------------|
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65 | DEHP |
| RoHS Certification | N/A |

ACCESSORIES



178PA28A

Freeze Probe Kit, 10k OHM, For MultiWave systems



124-00066

Insulator for 3-Circuit Timers



6T1396

Cover, Beige plastic