

Electronic Timer Control - 24-Hour Electronic Time Control, 3-Circuit, Type 3R Metal Enclosure

Item PE153



PRODUCT DESCRIPTION

This multipurpose 24-hour control is capable of automatically switching loads according to a preset daily schedule. Controls single- and two-speed pumps and cleaner/booster pumps. Three ON/OFF events per circuit per day.

FEATURES

- ▶ Controls single- and two-speed pumps and cleaner/booster pumps
- ▶ Three ON/OFF events per circuit per day
- ▶ Seven preprogrammed modes
- ▶ Freeze and heater protection
- ▶ LCD readout
- ▶ Multi-voltage input and output
- ▶ Countdown and override features enable programs to be overridden and automatically resumed without requiring the user to reprogram the system

APPLICATIONS

- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

| General                           |   |
|-----------------------------------|---|
| Model Number                      | PE153   |
| Description                       | 24-Hour Electronic Time Control, 3-Circuit, Type 3R Metal Enclosure |
| UPC Code                          | 078275092358  |
| Brand                             | Intermatic  |
| Country of Origin (Intermatic)    | CANADA  |
| Warranty Period                   | 1-Year limited  |
| Control Specifications            |   |
| Maximum ON/OFF Operations         | 3   |
| Operation Mode                    | 24 hour   |
| Mechanical Specifications         |   |
| Enclosure Type                    | Outdoor type 3R metal   |
| Dimensions                        |   |
| Product Dimensions (H x W x D) in | 9.375 x 5.5 x 3.625 in  |
| Material Specifications           |   |
| Color                             | Black   |
| Communication Method              |   |
| Has WiFi                          | No  |
| Load Ratings                      |   |
| Tungsten Range(s)                 | 5 A, 120/240 VAC, 50/60 Hz  |
| Resistive Load Ratings Ranges     | 17 A, 120/240 VAC, 50/60 Hz   |



Motor Load Ratings Ranges

80 LRA @ 120/240 VAC, 50/60 Hz; 17 FLA @ 120/240 VAC, 50/60 Hz

| Electrical Specifications |                       |
|---------------------------|-----------------------|
| Voltage Selection Type    | Multi-Voltage         |
| Input Voltage Range(s)    | 120/240 VAC, 50/60 Hz |
| Number of Circuits        | 3                     |
| Switch Type               | 3-SPST                |
| Hz                        | 50/60                 |

| Packaging                             |                           |
|---------------------------------------|---------------------------|
| Shipping Weight (lbs)                 | 3.802                     |
| Unit Carton Dimensions (H x W x L) in | 4.251 x 7.251 x 11.501 in |

| Standards and Certifications             |              |
|--|--------------|
| CSA Certification                        | cCSAus       |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65                | DEHP         |
| RoHS Certification                       | N/A          |