

## Surge Strip Protection Device - Surge Protective Device, Point-of-use strip, White, 3-Mode, 4 Outlets, 125 VAC, Type 3, Connected Equipment Warranty 5 yr \$10,000

Item IG112463



### PRODUCT DESCRIPTION

Type 3 Point-of-Use Surge Protective Devices (SPD) are designed for heavy industrial use with 3 modes of surge protection (L-N, L-G, N-G). Features a 15 A resettable breaker and #14 AWG SJT power cord with molded plug. CSA certified to ANSI/UL 1449, 5th Edition.

### FEATURES

- ▶ Three Modes of protection
- ▶ Metal Oxide Varistor (MOV) surge protection technology
- ▶ 15 A resettable breaker
- ▶ #14 AWG SJT power cord with molded plug
- ▶ Six foot cord length with four outlets
- ▶ LED protection indicator
- ▶ White
- ▶ Extruded aluminum housing
- ▶ Illuminating ON/OFF Switch
- ▶ 5-year product warranty

### APPLICATIONS

- ▶ Surge Protection

### TECHNICAL DATA

#### General

Model Number	IG112463
Description	Surge Protective Device, Point-of-use strip, White, 3-Mode, 4 Outlets, 125 VAC, Type 3, Connected Equipment Warranty 5 yr \$10,000
UPC Code	078275124530
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	5-Year limited
Connected Equipment Warranty Period	5-Year

#### Control Specifications

Surge Protection Type	3
Has Illuminated ON/OFF Switch	Yes

#### Mechanical Specifications

Number of Outlets	4
-------------------	---

#### Dimensions

Product Dimensions (H x W x D) in	1.875 x 1.875 x 9.563 in
Cord Length (ft)	6
Cord Length (m)	1.828

#### Material Specifications

Color	White
-------	-------

**Electrical Specifications**

Maximum Continuous Operating Voltage (L-G)	130
Maximum Continuous Operating Voltage (L-N)	130
Maximum Continuous Operating Voltage (N-G)	130
Voltage Protection Rating (L-N)	700
Circuit Breaker Amperage	15 A
Voltage Protection Rating (L-G)	600
Surge Protection Technology	MOV
Voltage Protection Rating (N-G)	600
Hz	60

**Packaging**

Shipping Weight (lbs)	1.846
Unit Carton Dimensions (H x W x L) in	3.25 x 5 x 10.75 in

**Environmental Specifications**

Temperature (operation)	-4 °F to 104 °F / (-20 °C to 40 °C)
-------------------------	-------------------------------------

**Standards and Certifications**

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
UL Standard	ANSI/UL 1449 5th Edition
California Proposition 65	DEHP
RoHS Certification	N/A

---

## ACCESSORIES



24EG5133

Mounting Bracket Plate for Type 3 SPD Surge Strips