

## Surge Strip Protection Device - Surge Protective Device, Point-of-use strip, White, 3-Mode, 6 Outlets, 125 VAC, Type 3, Connected Equipment Warranty 5 yr \$25,000

Item IG206153



### PRODUCT DESCRIPTION

Type 3 Point-of-Use Surge Protective Devices (SPD) are designed for heavy industrial use with 3 modes of surge protection (L-N, L-G, N-G). Features a 15 A resettable breaker and #14 AWG SJT power cord with molded plug. CSA certified to ANSI/UL 1449, 5th Edition.

### FEATURES

- Three Modes of protection
- Metal Oxide Varistor (MOV) surge protection technology
- 15 A resettable breaker
- #14 AWG SJT power cord with molded plug
- Fifteen foot cord with six outlets
- LED protection indicator
- EMI/RFI Noise Filtration
- Extruded aluminum housing
- White
- 5-year product warranty

### APPLICATIONS

- Surge Protection

### TECHNICAL DATA

#### General

Model Number	IG206153
Description	Surge Protective Device, Point-of-use strip, White, 3-Mode, 6 Outlets, 125 VAC, Type 3, Connected Equipment Warranty 5 yr \$25,000
UPC Code	078275124585
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	5-Year limited
Connected Equipment Warranty Period	5-Year

#### Control Specifications

Surge Protection Type	3
-----------------------	---

#### Mechanical Specifications

Number of Outlets	6
-------------------	---

#### Dimensions

Product Dimensions (H x W x D) in	1.875 x 1.875 x 15.75 in
Cord Length (ft)	15
Cord Length (m)	4.572

#### Material Specifications

Color	White
-------	-------

#### Electrical Specifications

Maximum Continuous Operating Voltage (L-G)	130
Maximum Continuous Operating Voltage (L-N)	130
Maximum Continuous Operating Voltage (N-G)	130
Voltage Protection Rating (L-N)	400
Circuit Breaker Amperage	15 A
Voltage Protection Rating (L-G)	400
Surge Protection Technology	MOV
Voltage Protection Rating (N-G)	500
Has EMI/RFI Noise Filtration	Yes

**Packaging**

Shipping Weight (lbs)	3.493
Unit Carton Dimensions (H x W x L) in	3 x 5 x 16.5 in

**Environmental Specifications**

Temperature (operation)	-4 °F to 104 °F / (-20 °C to 40 °C)
-------------------------	-------------------------------------

**Standards and Certifications**

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
UL Standard	ANSI/UL 1449 5th Edition
California Proposition 65	DEHP
RoHS Certification	N/A

---

**ACCESSORIES**



24EG5133

Mounting Bracket Plate for Type 3 SPD Surge Strips