

Mechanical Time Switch - 24-Hour Mechanical Time Switch, 120 VAC, 60Hz, SPST, Indoor Metal Enclosure, 1 Hour Interval

Item T101



PRODUCT DESCRIPTION

The T101 Series Mechanical Time Switch has proven it can stand the test of time. These dependable time switches can handle electrical loads up to 40 A per pole and allow for up to 12 ON/OFF operations per day. A manual override switch provides added convenience.

FEATURES

- Direct 24-hour control of most loads
- Up to 12 ON/OFF operations each day with minimum ON/OFF times of one hour
- Manual override
- One ON and one OFF tripper included

APPLICATIONS

- Timing/Scheduling ON/OFF
- Indoor Lighting Control

TECHNICAL DATA

General

Model Number	T101
Description	24-Hour Mechanical Time Switch, 120 VAC, 60Hz, SPST, Indoor Metal Enclosure, 1 Hour Interval
UPC Code	078275000018
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Control Specifications

Minimum ON/OFF Times	1 hour
Maximum ON/OFF Operations	12
Skipper Wheel	Not Included
Timing Interval	1 hr
Operation Mode	24 hour
Has Manual Override	Yes
Application Compatibilities	LED; HID

Mechanical Specifications

Enclosure Type	Indoor type 1 metal
Number of Trippers Included	1 ON/1 OFF

Dimensions

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

Material Specifications

Color	Gray
-------	------

Load Ratings

Tungsten Range(s)	40 A, 120 VAC, 60 Hz
Electronic Ballast	16 A
Electronic Ballast Load Ratings Ranges	16 A, 120 VAC
Inductive	40 A, 120 VAC, 60 Hz
Resistive Load Ratings Ranges	40 A, 120 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120 VAC, 60 Hz
Pilot Duty Load Ratings Ranges	1000 VA, 120 VAC, 60 Hz
Motor Load Ratings Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz

Electrical Specifications

Wiring Option	Terminals
Input Voltage Range(s)	120 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPST
Maximum Power Consumption (W)	3 W
Hz	60

Packaging

Shipping Weight (lbs)	2.744
Unit Carton Dimensions (H x W x L) in	8.25 x 3.5 x 5.5 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED; Green Energy
UL File Number	UL917
California Proposition 65	Lead
RoHS Certification	N/A

ACCESSORIES



156T1978AMX

1 Set of ON/OFF Trippers for T100, T7000, and WH40



156T1978A

Extra/replacement trippers 1 ON and 2 OFF



156T1978AD12

12 Pack of 156T1978A Trippers for T100, T7000, and WH40



22T338GR

Mounting Bracket for Intermatic Standardized Timer Mechanisms



124T1948

Insulator for Single-Pole Time Switch (T101, T102, T171, T172)



WG1570-10D

125 VAC, 60 Hz Motor for T101, T103, 125 VAC, 60 Hz Motor for T101, T103, T105



WG1570-10DMX

125 VAC, 60 Hz Motor for T101, T103, 125 VAC, 60 Hz Motor for T101, T103, T105