# Cartridge Filters - 200 Sq Ft Standard Apex Cartridge Filter (tall) System with 2-Speed, 1.5 HP pump, 6 Ft cord and standard plug

Item APA152SP63200CFK

## PRODUCT DESCRIPTION

We partnered our energy efficient two-speed Purflo pumps with our highly effective Apex series cartridge filters that remove dirt and debris down to 20 microns. This complete solution will keep your pool cleaner with minimal maintenance.

## FEATURES

► Now with a 2-year limited warranty on parts (Effective May 1, 2025)
► Quiet and DOE compliant Purflo 2-speed pump.
► Single cartridge element.
► Totally enclosed fan-cooled (TEFC) pool pump technology.
► Quick change cartridge filters with 1/2 turn secure-n-lock replacement.
► Easy-to-read pressure gauge allows for quick performance assessment.
► Self-priming pump. No backwashing required.
► Large drain plug.
► Constructed of corrosion-proof reinforced thermoplastic tank for long service life.
► Manual air relief valve pre-installed from the factory and a 6 ft. cord with a standard plug.

## APPLICATIONS

► Above Ground Pools

## TECHNICAL DATA

| General | |
|---|---|
| Model Number | APA152SP63200CFK |
| Description | 200 Sq Ft Standard Apex Cartridge Filter (tall) System with 2-Speed, 1.5 HP pump, 6 Ft cord and standard plug |
| UPC Code | 078275156784 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | U.S.A. |
| Warranty Period | 2-Year limited |
| Filter Area (Sq Ft) | 200 |
| Min Service Clearance | 46" |
| Filter Element Height | 34" |
| Cartridges Required | 1 |
| Turnover Capacity 6 hour (gallons) | 36,000 |
| Turnover Capacity 8 hour (gallons) | 48,000 |
| Turnover Capacity 10 hour (gallons) | 60,000 |
| Max Working PSI | 50 |
| Replacement Filter Element | 62557-AQP1 |
| Turnover Capacity 6 hour Max Flow (gallons) | 54,000 |
| Turnover Capacity 8 hour Max Flow (gallons) | 72,000 |
| Turnover Capacity 10 hour Max Flow (gallons) | 90,000 |
| Maximum Flow Rate (GPM) | 150 |

| Material Specifications | |
|---|---|
| Color | Black |

Technical specifications and other information are subject to change without notice. Images can vary from original.

© 02/17/2026   1/2

## Packaging

| | |
|---|---|
| Shipping Weight (lbs) | 58 |
| Unit Carton Dimensions (H x W x L) in | 34 x 26 x 17 in |
| Unit Package Quantity | 1 |

## Operating Specifications

| | |
|---|---|
| Recommended Water Flow GPM | 100 |

## Standards and Certifications

| | |
|---|---|
| California Proposition 65 | Lead |
| RoHS Certification | N/A |