INTERMATIC

Cartridge Filters - 48 Sq Ft Diatomaceous Earth (DE) Filter (tall) System with 2-Speed, 1.5 HP pump, 6 Ft cord and standard plug

Item APA152SP63048TDFK

PRODUCT DESCRIPTION

We partnered our energy efficient 2 speed Purflo pumps with our highly effective D.E. filters that remove dirt and debris down to 5 microns. This complete solution will keep your pool cleaner with minimal maintenance.

FEATURES

► Now with a 2-year limited warranty on parts (Effective May 1, 2025)
► Quiet and DOE compliant Purflo 2-speed pump.
► Single D.E. (Diatomaceous Earth) element.
► Totally enclosed fan-cooled (TEFC) pool pump technology.
► Quick change cartridge filters with 1/2 turn secure-n-lock replacement.
► Easy-to-read pressure gauge allows for quick performance assessment.
► Self-priming pump. Large drain plug.
► Constructed of corrosion-proof reinforced thermoplastic tank for long service life.
► Manual air relief valve pre-installed from the factory.
► 6 ft. Cord with a standard plug.

APPLICATIONS

► Above Ground Pools

TECHNICAL DATA

General	
Model Number	APA152SP63048TDFK
Description	48 Sq Ft Diatomaceous Earth (DE) Filter (tall) System with 2-Speed, 1.5 HP pump, 6 Ft cord and standard plug
UPC Code	078275156678
Brand	Intermatic
Country of Origin (Intermatic)	U.S.A.
Warranty Period	2-Year limited
Filter Area (Sq Ft)	48
Min Service Clearance	46"
Filter Element Height	34"
Cartridges Required	1
Diatomaceous Earth Required	4.5 lbs
Turnover Capacity 6 hour (gallons)	34,560
Turnover Capacity 8 hour (gallons)	46,080
Turnover Capacity 10 hour (gallons)	57,600
Max Working PSI	50
Replacement Filter Element	62551-AQP1
Turnover Capacity 6 hour Max Flow (gallons)	43,200
Turnover Capacity 8 hour Max Flow (gallons)	57,600
Turnover Capacity 10 hour Max Flow (gallons)	72,000
Maximum Flow Rate (GPM)	120

Material Specifications	
Color	Black

Packaging

Shipping Weight (lbs)	34.577
Unit Carton Dimensions (H x W x L) in	34 x 26 x 17 in
Unit Package Quantity	1

Operating Specifications

Recommended Water Flow GPM	96

Standards and Certifications

California Proposition 65	Lead
RoHS Certification	N/A

Packaging

Shipping Weight (lbs)	34.577