

## Cartridge Filters - 150 Sq Ft Standard Apex Cartridge Filter (tall) System with 2-Speed, 2 HP pump, 6 Ft cord and standard plug

Item APA202SP63150CFK



### PRODUCT DESCRIPTION

We partnered our energy efficient 2 speed Purflo pumps with our highly effective Apex series cartridge filters that remove dirt and debris down to 20 microns. This complete solution will keep your pool cleaner with minimal maintenance.

### FEATURES

- ▶ Now with a 2-year limited warranty on parts (Effective May 1, 2025)
- ▶ Quiet and DOE compliant Purflo 2-speed pump.
- ▶ Single cartridge element.
- ▶ Totally enclosed fan-cooled (TEFC) pool pump technology.
- ▶ Quick change cartridge filters with 1/2 turn secure-n-lock replacement.
- ▶ Easy-to-read pressure gauge allows for quick performance assessment.
- ▶ Self-priming pump. No backwashing required.
- ▶ Large drain plug.
- ▶ Constructed of corrosion-proof reinforced thermoplastic tank for long service life.
- ▶ Manual air relief valve pre-installed from the factory and a 6 ft. cord with a standard plug.

### APPLICATIONS

- ▶ Above Ground Pools

### TECHNICAL DATA

General	
Model Number	APA202SP63150CFK
Description	150 Sq Ft Standard Apex Cartridge Filter (tall) System with 2-Speed, 2 HP pump, 6 Ft cord and standard plug
UPC Code	816965015801
Brand	Intermatic
Country of Origin (Intermatic)	U.S.A.
Warranty Period	2-Year limited
Filter Area (Sq Ft)	150
Min Service Clearance	46"
Filter Element Height	34"
Cartridges Required	1
Turnover Capacity 6 hour (gallons)	27,000
Turnover Capacity 8 hour (gallons)	36,000
Turnover Capacity 10 hour (gallons)	45,000
Max Working PSI	50
Replacement Filter Element	62556-AQP8
Turnover Capacity 6 hour Max Flow (gallons)	54,000
Turnover Capacity 8 hour Max Flow (gallons)	72,000
Turnover Capacity 10 hour Max Flow (gallons)	90,000
Maximum Flow Rate (GPM)	150

### Material Specifications

Color	Black
-------	-------

**Packaging**

Shipping Weight (lbs)	58
Unit Carton Dimensions (H x W x L) in	34 x 26 x 17 in
Unit Package Quantity	1

**Operating Specifications**

Recommended Water Flow GPM	75
----------------------------	----

**Standards and Certifications**

California Proposition 65	Lead
RoHS Certification	N/A