

## Cartridge Filters - 72 Sq Ft Diatomaceous Earth (DE) Filter (tall) System with 2-Speed, 2 HP pump, 6 Ft cord and standard plug

Item APA202SP63072DFK



### PRODUCT DESCRIPTION

We partnered our energy efficient 2 speed Purflo pumps with our highly effective D.E. filters that remove dirt and debris down to 5 microns. This complete solution will keep your pool cleaner with minimal maintenance.

### FEATURES

- ▶ Now with a 2-year limited warranty on parts (Effective May 1, 2025)
- ▶ Quiet and DOE compliant Purflo 2-speed pump.
- ▶ Single D.E. (Diatomaceous Earth) element.
- ▶ Totally enclosed fan-cooled (TEFC) pool pump technology.
- ▶ Quick change cartridge filters with 1/2 turn secure-n-lock replacement.
- ▶ Easy-to-read pressure gauge allows for quick performance assessment.
- ▶ Self-priming pump. Large drain plug.
- ▶ Constructed of corrosion-proof reinforced thermoplastic tank for long service life.
- ▶ Manual air relief valve pre-installed from the factory.
- ▶ 6 ft. Cord with a standard plug.

### APPLICATIONS

- ▶ Above Ground Pools

### TECHNICAL DATA

General	
Model Number	APA202SP63072DFK
Description	72 Sq Ft Diatomaceous Earth (DE) Filter (tall) System with 2-Speed, 2 HP pump, 6 Ft cord and standard plug
UPC Code	816965014217
Brand	Intermatic
Country of Origin (Intermatic)	U.S.A.
Warranty Period	2-Year limited
Filter Area (Sq Ft)	72
Min Service Clearance	46"
Filter Element Height	34"
Cartridges Required	1
Diatomaceous Earth Required	6.5 lbs
Turnover Capacity 6 hour (gallons)	51,840
Turnover Capacity 8 hour (gallons)	69,120
Turnover Capacity 10 hour (gallons)	86,400
Max Working PSI	50
Replacement Filter Element	62552-AQP1
Turnover Capacity 6 hour Max Flow (gallons)	54,000
Turnover Capacity 8 hour Max Flow (gallons)	72,000
Turnover Capacity 10 hour Max Flow (gallons)	90,000
Maximum Flow Rate (GPM)	150
Material Specifications	
Color	Black

**Packaging**

Shipping Weight (lbs)	66
Unit Carton Dimensions (H x W x L) in	34 x 26 x 17 in
Unit Package Quantity	1

**Operating Specifications**

Recommended Water Flow GPM	144
----------------------------	-----

**Standards and Certifications**

California Proposition 65	Lead
RoHS Certification	N/A