

Graesslin Mechanical Time Switch - 24-Hour 208/240V Electromechanical Timer, 15 Minute Intervals, 21A, SPDT, Type 1 Indoor Plastic Enclosure

Item GMXST-I-240



PRODUCT DESCRIPTION

The GMX series time switches are universal mechanical time switches. They are a low cost alternative for applications that do not require more than 21 A or 2 HP @ 240 VAC. The timer is mounted in a UL Type 1 indoor or Type 3R outdoor plastic enclosure. The GMX is a light-duty commercial time switch ideal for 24, 120 or 208/240 VAC single-phase general applications.

FEATURES

- ▶ 21 A SPDT Switch
- ▶ UL Type 1 indoor or Type 3R outdoor plastic enclosure
- ▶ Manual 3-way override
- ▶ Captive trippers with 15-minute intervals on 24-hour models and 2-hour intervals on 7-day models
- ▶ True clock face, easy to set
- ▶ Finger-safe terminals
- ▶ Enclosure provides space for field-added contactor or other accessories

APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

TECHNICAL DATA

General	
Model Number	GMXST-I-240
Description	24-Hour 208/240V Electromechanical Timer, 15 Minute Intervals, 21A, SPDT, Type 1 Indoor Plastic Enclosure
UPC Code	078275153240
Brand	Domestic Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Control Specifications	
Maximum Cycle Time	24 hrs
Timing Interval	15 min
Clock Drive Type	Synchronous
Mechanism Type	Electromechanical
Has Captive Trippers	Yes
Has Override Switch	Yes
Has Real-time Clock Face	Yes
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications	
Mounting Options	Wall
Enclosure Type	Indoor type 1 plastic
Number of Trippers Included	96

Has Finger-Safe Terminals	Yes
---------------------------	-----

Dimensions

Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
-----------------------------------	-----------------

Wire Size Max	#12 AWG
---------------	---------

Load Ratings

Motor Load Ratings Ranges	1 HP, 120 VAC; 2 HP, 250 VAC
---------------------------	------------------------------

Electrical Specifications

Maximum Power Consumption (VA)	1
--------------------------------	---

Wiring Option	Screw terminal accepts up to #12 AWG wire
---------------	---

Switch Type	SPDT
-------------	------

Display and Format

Shortest switching time	ON/OFF 15 minutes
-------------------------	-------------------

Packaging

Shipping Weight (lbs)	1.547
-----------------------	-------

Unit Carton Dimensions (H x W x L) in	4.125 x 6.875 x 10.125 in
---------------------------------------	---------------------------

Environmental Specifications

Operating Humidity	0 to 95%, Non-condensing
--------------------	--------------------------

Temperature (operation)	-40 °F to 185 °F / (-40 °C to 85 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
------------------	-------

Other Certifications and Compatibilities	Green Energy
--	--------------

UL File Number	E10694
----------------	--------

California Proposition 65	None
---------------------------	------

RoHS Certification	N/A
--------------------	-----