

Item Bundle - 125 A Load Center with Compartment for Optional Wiring Devices, 8-Breaker Spaces

Item T4000R4



PRODUCT DESCRIPTION

Can be used as a Load Center only, or add mechanisms or wiring devices for complete control systems.

FEATURES

- ▶ Eight breaker spaces
- ▶ Reduces installation costs
- ▶ All-in-one electrical load center eliminates the need for additional service panels
- ▶ Accepts any combination of PF1000M Series, P1403ME, P1353ME, P4043ME, P4243ME, T100M Series or RC2000M Series mechanisms
- ▶ Fully compatible with all electrical requirements for pool/spa installations
- ▶ Load center dead front has four knockouts for switches or GFCl's (Note: T4000R4 has one knockout)
- ▶ Wiring devices may be installed in these Load Centers with the use of Standoffs, sold separately

APPLICATIONS

- ▶ Distribution/Control Panel

TECHNICAL DATA

General

Model Number	T4000R4
Description	125 A Load Center with Compartment for Optional Wiring Devices, 8-Breaker Spaces
UPC Code	078275043077
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications

Number of Breaker Knockouts	8
Enclosure Type	3R Beige metal

Dimensions

Product Dimensions (H x W x D) in	20.875 x 12.875 x 4.75 in
Knockout Dimensions Bottom	(5) 1/2" - 3/4", (4) 1/2", (2) 3/4" - 1", 1 1/4"
Knockout Dimensions Back	(4) 1/2" - 3/4", (2) 3/4" - 1"
Knockout Dimensions Left	(2) 1/2" - 3/4"
Knockout Dimensions Right	(1) 1 3/4" x 2 3/4"

Material Specifications

Color	Beige
-------	-------

Load Ratings

Mechanisms	Load Center with Compartment for Optional Wiring Devices
------------	--

Electrical Specifications

Number of Receptacle/Switch Knockouts	1
---------------------------------------	---

Packaging

Shipping Weight (lbs)	19.36
Unit Carton Dimensions (H x W x L) in	6 x 14 x 22 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

CSA Certification	cCSAus
California Proposition 65	None

ACCESSORIES



156T1978A
Extra/replacement trippers 1 ON and 1 OFF



21T166A
Spacer-Standoff, 3" long - 2 pack



21T156A
Spacer-Standoff, 3" long - 4 pack



124T1952
Insulator for Double-Pole Time Switch (T103, T104, T105, T173, T174, T175, T176, T185, WH40)



WP1000C
Plastic In-Use Weatherproof Cover, Single-Gang, Vrt, 2.25" Clear



22T338GR
Mounting Bracket for Intermatic Standardized Timer Mechanisms