

## Occupancy Sensor - Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only

Item IOS-CMP-UMX

**NOM**

### PRODUCT DESCRIPTION

The IOS-CMP-U 360° Passive Infrared (PIR) Line Voltage Occupancy Sensors control lighting systems based on occupancy and ambient light levels. When movement is detected, the sensor turns the lights ON. If no movement is detected for a user-specified time, the lights are turned OFF. The occupancy sensor provides a 360° coverage pattern, up to 1200 square feet.

### FEATURES

- ▶ PIR technology sensing for presence detection
- ▶ Coverage: 1200 ft<sup>2</sup> when mounted on 8 to 11 ft ceiling
- ▶ Zero-crossing technology for long life and performance
- ▶ Adjustable ambient light sensor override
- ▶ Requires neutral connection
- ▶ Incandescent/Fluorescent/CFL/LED compatible

### APPLICATIONS

- ▶ Indoor Sensing Control

### TECHNICAL DATA

#### General

Model Number	IOS-CMP-UMX
Description	Commercial Grade Line Voltage Ceiling Mount PIR Occupancy Sensor, White, Mexico Sales Only
UPC Code	078275139916
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA

#### Control Specifications

Sensor Switch Type	Occupancy
Sensor Technology	PIR (Passive Infrared)
Adjustable Time Delay Min	15 sec
Adjustable Time Delay Max	30 min
Adjustable Light Level Min	10 fc
Adjustable Light Level Max	150 fc
PIR Coverage Area (sq ft)	1200
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

#### Mechanical Specifications

PIR Coverage Pattern (degrees)	360
Maximum Mounting Height (ft)	8-11 ft
Mount Type	Ceiling

#### Dimensions

Product Height (in)	1.375
Product Height (mm)	35
Product Diameter (in)	4.563

Product Diameter (mm)	116
-----------------------	-----

**Material Specifications**

Color	White
Includes Wall Plate	Yes

**Load Ratings**

Tungsten Range(s)	800 W, 120/125 VAC
Resistive Load Ratings Ranges	10 A, 120/125 VAC
Motor Load Ratings Ranges	1/4 HP, 120/125 VAC
Electronic Ballast Load Ratings Ranges	800 VA, 120/125 VAC; 1600 VA, 277 VAC

**Electrical Specifications**

Input Voltage Range(s)	120/277 VAC, 60 Hz
Occupancy Sensor Power Type	Line Voltage
Neutral Connection Required	Yes
Hz	60

**Packaging**

Shipping Weight (lbs)	0.4
Shipping Weight (kg)	0.181
Unit Carton Dimensions (H x W x L) in	2 x 5 x 5 in

**Environmental Specifications**

Temperature (operation)	32 - 131°F / 0 - 55°C
-------------------------	-----------------------

**Standards and Certifications**

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A