

In-Wall Timer - 7-Day Standard Programmable Timer, 125 VAC, 15A, Light Almond

Item EI500LAC



PRODUCT DESCRIPTION

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

FEATURES

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Single-pole circuit
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection
- ▶ Backlit LCD display
- ▶ Decorator switch plate not included

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	EI500LAC
Description	7-Day Standard Programmable Timer, 125 VAC, 15A, Light Almond
UPC Code	078275105225
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications	
Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	14
Time Presets	Flexible
Operation Mode	24 hour
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Service Type	Non-Replaceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Chemical Composition of the Battery Cell	Ni-MH
Number of Batteries Included	1
Battery Weight (grams)	3.5
Number of Lithium-ion Cells in Battery	N/A
Number of Lithium Metal Cells in Battery	N/A
Watt Hours Per Battery	0.096
Lithium Content (grams) in Battery	N/A

Mechanical Specifications

Wall Plate Configurations

Single-Gang

Dimensions

Product Dimensions (H x W x D) in 4.125 x 1.75 x 1.438 in

Material Specifications

Color Light Almond
 Includes Wall Plate No
 Finish Gloss

Load Ratings

General Purpose 15 A, 1875 W
 Resistive Heater 15 A, 1875 W
 Tungsten (Incandescent) Range(s) 1000 W
 Ballast Fluorescent 8 A, 1000 VA
 Electronic Ballast LED 4 A, 500 VA
 Motor Load Ratings Ranges 1/4 HP, 125 VAC, 60 Hz
 Inductive Load Ratings Ranges 1000 VA, 125 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s) 125 VAC, 60 Hz
 Wiring Configurations Single
 Neutral Connection Required Yes
 Watts 1875
 Hz 60
 Amperage 15 A

Environmental Specifications

Temperature (operation) 32 - 104 °F / 0 - 40 °C

Packaging

Shipping Weight (lbs) 0.351
 Unit Carton Dimensions (H x W x D) in 4.88 x 3 x 2.13 in

Standards and Certifications

UL Certification cULus
 Other Certifications and Compatibilities Green Energy
 California Proposition 65 DEHP
 RoHS Certification N/A