

## Plug-In Timer -

Item TN311MX



**NOM**

### PRODUCT DESCRIPTION

The TN311 Series provides a quick and easy way to automate ON/OFF schedules and plugs directly into standard wall outlets.

### FEATURES

- ▶ 3 ON/3 OFF settings per day with removable trippers, more ON/OFF events with addition of extra trippers
- ▶ Minimum 30-min ON/OFF time
- ▶ Grounded receptacle and 3-prong plug
- ▶ Plugs directly into wall outlet

### APPLICATIONS

- ▶ Air Movement & Ventilation
- ▶ Indoor Lighting Control

### TECHNICAL DATA

#### General

|                                |                |
|--------------------------------|----------------|
| Model Number                   | TN311MX        |
| UPC Code                       | 078275127890   |
| Brand                          | Intermatic     |
| Country of Origin (Intermatic) | MEXICO         |
| Warranty Period                | 5-Year limited |
| TARIC HS Code                  | 9107.00.00     |

#### Control Specifications

|                      |                   |
|----------------------|-------------------|
| Minimum ON/OFF Times | 30 min            |
| Operation Mode       | 24 hour           |
| Mechanism Type       | Analog/Mechanical |
| On Events            | 24                |
| Off Events           | 24                |
| Total Events         | 48                |

#### Mechanical Specifications

|                     |      |
|---------------------|------|
| Number of Plugs     | 1    |
| Plug Configurations | 5-15 |

#### Dimensions

|                                   |                 |
|-----------------------------------|-----------------|
| Product Dimensions (H x W x D) in | 3.11 x 3 x 2 in |
|-----------------------------------|-----------------|

#### Material Specifications

|       |       |
|-------|-------|
| Color | White |
|-------|-------|

#### Load Ratings

|                            |                        |
|----------------------------|------------------------|
| Incandescent Load Ratings  | 1875 W, 125 VAC, 60 Hz |
| Ballast Fluorescent Ranges | 15 A, 125 VAC          |
| Motor Load Ratings Ranges  | 1/3 HP, 125 VAC, 60 Hz |

**Electrical Specifications**

|                        |                |
|------------------------|----------------|
| Input Voltage Range(s) | 125 VAC, 60 Hz |
| Hz                     | 60             |

**Packaging**

|                                       |                      |
|---------------------------------------|----------------------|
| Shipping Weight (lbs)                 | 0.42                 |
| Unit Carton Dimensions (H x W x L) in | 3.15 x 3.15 x 3.2 in |

**Environmental Specifications**

|                    |        |
|--------------------|--------|
| Usage Environments | Indoor |
|--------------------|--------|

**Standards and Certifications**

|  |      |
|--|------|
| Other Certifications and Compatibilities | NOM  |
| California Proposition 65                | None |
| RoHS Certification                       | N/A  |

---

## ACCESSORIES



107TN221

Red (OFF) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS



107TN222

Turquoise (ON) tripper for TN, PB, TB Series, P1101, P1131, P1161, P1261P, AL300TPWS, AL600TPWS and AL900TPWS