

Photocontrol - NIGHTFOX Standard Grade Locking Type Electronic Photocontrol, 120-277 V, Mexico Sales Only

Item ELC4536MX



NOM

PRODUCT DESCRIPTION

LED-compatible photocontrol features a 10-year life expectancy. Ideal for single fixture control of smaller LED fixtures that require a cost-effective solution.

FEATURES

- ▶ Non-drift silicon light sensor with IR filter
- ▶ All components meet 10-year life expectancy
- ▶ Exceeds 5,000 ON/OFF switching cycles
- ▶ Ideal for single HID and LED fixtures (up to 550 W @ 277 VAC)
- ▶ Power-up ON delay (45-60 sec) for easy installation verification and troubleshooting
- ▶ 510 J MOV surge protection

APPLICATIONS

- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

| | |
|--------------------------------|--|
| Model Number | ELC4536MX |
| Description | NIGHTFOX Standard Grade Locking Type Electronic Photocontrol, 120-277 V, Mexico Sales Only |
| UPC Code | 078275142961 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | MEXICO |
| Warranty Period | 6-Year limited |

Control Specifications

| | |
|------------------------------|--------------------------------|
| Sensor Time Delay | Instant ON; 2 sec to 5 sec OFF |
| Photocell Type | Silicon Diode |
| Photo Control Switch Type | Relay |
| Fail Mode | ON |
| Activation On | 1.5 fc |
| Activation Off | 2.25 fc |
| Photocontrol Type | Electronic |
| Application Compatibilities | LED; Incandescent; HID |
| Photocontrol Style | Locking type |
| Photocontrol Sensor Location | Side |

Dimensions

| | |
|-----------------------|-------|
| Product Height (in) | 2.75 |
| Product Height (mm) | 69.9 |
| Product Diameter (in) | 3.375 |
| Product Diameter (mm) | 85.8 |

Material Specifications

| | |
|-------|------|
| Color | Blue |
|-------|------|

| | |
|------------------|-----------------------------------|
| Housing Material | Polycarbonate with Acrylic Window |
|------------------|-----------------------------------|

Load Ratings

| | |
|---|----------------------------|
| Tungsten Range(s) | 1000 W |
| Magnetic Ballast (NO) Range(s) | 1800 VA |
| Electronic Ballast Load Ratings NO Ranges | 2 A, 120-277 VAC, 50/60 Hz |

Electrical Specifications

| | |
|-----------------------------|-----------------------|
| Input Voltage Range(s) | 120-277 VAC, 50/60 Hz |
| Surge Protection Technology | 510 J MOV |
| Hz | 50/60 |

Packaging

| | |
|---------------------------------------|-----------------------|
| Shipping Weight (lbs) | 0.27 |
| Unit Carton Dimensions (H x W x D) in | 3.25 x 3.25 x 3.25 in |

Operating Specifications

| | |
|--------------------------------|------|
| Expected Lifetime (Years) | 10 |
| Expected Lifetime (Operations) | 5000 |

Environmental Specifications

| | |
|-------------------------|--------------------------------------|
| Temperature (operation) | -40 °F to 158 °F / (-40 °C to 70 °C) |
| Usage Environments | Outdoor |

Standards and Certifications

| | |
|--|------|
| Other Certifications and Compatibilities | NOM |
| California Proposition 65 | None |
| RoHS Certification | N/A |

ACCESSORIES



K121
Locking Type Receptacle, 3-Pin,
C136.10 Compliant, 9" lead



K121-30
Locking Type Receptacle, 3-Pin,
C136.10 Compliant, 30" lead



K122
Locking Type Receptacle, 3-Pin,
C136.10 Compliant, with Pole
Mounting Bracket



KPT1170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Dusk-to-Dawn, 10' cable



KPT0170-010
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 10' cable



K171H
Locking Type Receptacle, 7-Pin,
C136.41 Compliant, 12" lead



SK4500K
Shorting Plug for Locking Type
Receptacles



KPT0170-015
PowerTap Receptacle, 7-Pin, C136.41
Compliant, Always-On, 15' cable



SK4500KMX
Shorting Plug for Locking Type
Receptacles