

## Plug-In Timer -

Item DT200LT



### PRODUCT DESCRIPTION

Digital 24-hour landscape timer with DST, rated for use in low voltage transformers up to 1200W featuring ON programming at Dusk or predetermined time and OFF at Dawn or predetermined time.

### FEATURES

- ▶ For use in low voltage transformers up to 1200 W
- ▶ Program ON at dusk or specific time
- ▶ Program OFF at dawn or specific time
- ▶ Automatic Daylight Savings Time adjustment
- ▶ Intermatic Linesync timing technology for years of accurate timing

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Landscape Water Control

### TECHNICAL DATA

#### General

Model Number	DT200LT
UPC Code	078275148901
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

#### Control Specifications

Minimum ON/OFF Times	1 min
Operation Features	Astronomic
Operation Mode	24 hour
Backup Type	Battery
Battery Type	LR44
Battery Service Type	Replaceable
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; HID; LED; CFL
Chemical Composition of the Battery Cell	Alkaline
Number of Batteries Included	2
On Events	1
Off Events	1
Total Events	2

#### Mechanical Specifications

Number of Plugs	2
Plug Configurations	5-15

#### Dimensions

Product Dimensions (H x W x D) in	3.188 x 3.307 x 2.224 in
-----------------------------------	--------------------------

**Material Specifications**

Color	Black
-------	-------

**Load Ratings**

Incandescent Load Ratings	1000 W, 120 VAC, 60 Hz
Inductive	12 A, 120 VAC
Motor Load Ratings Ranges	1/2 HP, 120 VAC, 60 Hz

**Electrical Specifications**

Input Voltage Range(s)	120 VAC, 60 Hz
Hz	60

**Packaging**

Shipping Weight (lbs)	0.509
Unit Carton Dimensions (H x W x L) in	3.375 x 3.375 x 3.062 in

**Environmental Specifications**

Usage Environments	Outdoor
--------------------	---------

**Standards and Certifications**

UL Certification	cULus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	None
RoHS Certification	N/A