

## Electronic Timer Control - Astronomic 7-Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor Metal Enclosure

Item ET8015C



### PRODUCT DESCRIPTION

This series offers an easy way to upgrade from a basic mechanical time switch to an electronic time switch. These timers will allow for up-to-the-minute programming, battery backup for power loss, up to 28 events total, and automatic daylight saving time corrections without the need of user interaction. They come in standard 7-day astronomic versions.

### FEATURES

- ▶ Selector switch to determine input voltage between 120-277 VAC
- ▶ Up to 28 events total
- ▶ To-the-minute accuracy
- ▶ Temporary override or permanent manual override
- ▶ Automatic Daylight Saving Time adjustment
- ▶ Astronomic models enable dusk-to-dawn scheduling

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Machinery & Pump Controls
- ▶ Timing/Scheduling ON/OFF

### TECHNICAL DATA

#### General

Model Number	ET8015C
Description	Astronomic 7-Day 1-Circuit Electronic Control, 120-277 VAC, SPST, Indoor Metal Enclosure
UPC Code	078275089754
Brand	Intermatic
Country of Origin (Intermatic)	THAILAND
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Times	Indefinite
Operation Features	Astronomic
Operation Mode	7 day
Daylight Savings Adjustment	Automatic
Backup Type	Battery
Battery Type	AAA
Battery Service Type	Replaceable
Chemical Composition of the Battery Cell	Alkaline
Number of Batteries Included	2
On Events	14
Off Events	14
Total Events	28 (+ Astronomic)

#### Mechanical Specifications

Enclosure Type	Indoor type 1 metal
----------------	---------------------

Dimensions	
Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

Material Specifications	
Color	Gray

Communication Method	
Has WiFi	No

Load Ratings	
Tungsten Range(s)	5 A, 120-240 VAC
Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
Resistive (NO) Range(s)	20 A, 28 VDC; 30 A, 120/240 VAC
Inductive Load Ratings NO Ranges	30 A, 120/240 VAC
Electronic Ballast Load Ratings NO Ranges	1 A, 120-277 VAC
Resistive Load Ratings Ranges	20 A, 28 VDC; 30 A, 120/240 VAC
Tungsten (NO) Range(s)	5 A, 120/240 VAC
Motor Load Ratings Ranges	1 HP, 120 VAC; 2 HP, 240 VAC
Motor Load Ratings NO Ranges	1 HP, 120 VAC; 2 HP, 240 VAC

Electrical Specifications	
Voltage Selection Type	Selector Switch
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Number of Circuits	1
Switch Type	SPST
Maximum Power Consumption (W)	6 W
Electronic Series	ET8000 Series
Hz	50/60
Amperage	30 A

Packaging	
Shipping Weight (lbs)	2.844
Unit Carton Dimensions (H x W x L) in	3.131 x 5.251 x 8.001 in

Environmental Specifications	
Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)

Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	Lead

RoHS Certification

N

---

## ACCESSORIES



124ET2581  
(SPST) Insulator for ET Series controls (ET1105C, ET1105CR,  
ET1705C, ET1705CR, ET8015C and ET8015CR)



ETBATT-1  
Battery Tray Door, ET Series