


In-Wall Timer -

Item KM2ST-2R



PRODUCT DESCRIPTION

For installing on circuits up to 20 A, this timer provides automatic 24-hour ON/OFF control of outdoor/indoor lighting, fans, pumps, office equipment and other types of loads.

FEATURES

- ▶ 72 trippers provide 36 ON/OFF events per 24-hour period
- ▶ Captive trippers with 20-minute switching intervals
- ▶ 3-way (SPDT) switch available
- ▶ 3-position ON/OFF/AUTO override provides continuous ON or OFF operation
- ▶ Reliable synchronous timer motor
- ▶ Multiple wall plates available
- ▶ Easy wiring and installation
- ▶ Heavy-Duty 20 A rating
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

| General                                |                                |
|----------------------------------------|--------------------------------|
| Model Number                           | KM2ST-2R                       |
| UPC Code                               | 614573043717                   |
| Brand                                  | Intermatic                     |
| Country of Origin (Intermatic)         | MEXICO                         |
| Warranty Period                        | 1-Year limited                 |
| Control Specifications                 |                                |
| Minimum ON/OFF Times                   | 20 min                         |
| Operation Mode                         | 24 hour                        |
| Mechanism Type                         | Analog/Mechanical              |
| Application Compatibilities            | Incandescent; Fluorescent; CFL |
| On Events                              | 36                             |
| Off Events                             | 36                             |
| Total Events                           | 72                             |
| Mechanical Specifications              |                                |
| Wall Plate Configurations              | 2-Gang                         |
| Material Specifications                |                                |
| Color                                  | White                          |
| Includes Wall Plate                    | Yes                            |
| Load Ratings                           |                                |
| Incandescent Load Ratings (Multi-Gang) | 1350 W, 120 VAC, 60 Hz         |
| Motor Load Ratings Ranges              | 1 HP, 120 VAC, 60 Hz           |



|                                             |                        |
|---------------------------------------------|------------------------|
| Inductive Load Ratings Ranges               | 8 A, 120 VAC, 60 Hz    |
| Incandescent Multi Gang Load Ratings Ranges | 1350 W, 120 VAC, 60 Hz |

Electrical Specifications

|                             |                                                            |
|-----------------------------|------------------------------------------------------------|
| Input Voltage Range(s)      | 120 VAC, 60 Hz                                             |
| Wiring Configurations       | Single                                                     |
| Switch Type                 | SPST                                                       |
| Neutral Connection Required | Yes                                                        |
| Wiring Option               | SPST (3) #14 AWG color coded; SPDT (4) #14 AWG color coded |
| Hz                          | 60                                                         |

Environmental Specifications

|                         |                            |
|-------------------------|----------------------------|
| Operating Humidity      | 0 to 95%, Non-condensing   |
| Temperature (operation) | -40 - 180 °F / -40 - 82 °C |

Packaging

|                                       |                     |
|---------------------------------------|---------------------|
| Shipping Weight (lbs)                 | 0.479               |
| Unit Carton Dimensions (H x W x D) in | 2.5 x 4.75 x 7.5 in |

Standards and Certifications

|                           |        |
|---------------------------|--------|
| UL Certification          | cULus  |
| CSA Certification         | cCSAus |
| California Proposition 65 | DEHP   |