

Mechanical Time Switch -

Item T104P3



PRODUCT DESCRIPTION

Heavy-duty mechanical time switches control a single load

FEATURES

- ▶ Highest motor load ratings in the industry
- ▶ 12 ON/OFF operations per day
- ▶ One ON and one OFF tripper included
- ▶ Available with pool heater protection
- ▶ Teeter-type terminals for multiple load connections

APPLICATIONS

- ▶ Heater Thermostat Control
- ▶ Motor Control
- ▶ Pump Control
- ▶ Water Circulation

TECHNICAL DATA

General	
Model Number	T104P3
UPC Code	078275026292
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Operation Mode	24 hour
Application Compatibilities	LED
On Events	12
Off Events	12
Total Events	24
Mechanical Specifications	
Enclosure Type	Outdoor type 3R plastic
Dimensions	
Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Knockout Dimensions Bottom	(2) 1/2" and 3/4"
Knockout Dimensions Back	1/2" and 3/4" combination
Material Specifications	
Color	Gray
Load Ratings	
Tungsten Range(s)	40 A, 120-277 VAC, 60 Hz
Inductive	40 A, 277 VAC, 60 Hz; 40 A, 240 VAC, 60 Hz; 40 A, 208 VAC, 60 Hz; 40 A, 120 VAC, 60 Hz

Electronic Ballast Load Ratings NO Ranges	16 A, 120-277 VAC
Resistive Load Ratings Ranges	40 A, 120-480 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120-277 VAC, 60 Hz
Pilot Duty Load Ratings Ranges	1000 VA, 120-277 VAC, 60 Hz
Motor Load Ratings Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz

Electrical Specifications

Heater Control Output	10 A, 250 VAC MAX, 60 Hz
Wiring Option	Terminals
Input Voltage Range(s)	208-277 VAC, 60 Hz
Number of Circuits	1
Switch Type	DPST
Maximum Power Consumption (W)	3 W
Hz	60
Amperage	40 A

Packaging

Shipping Weight (lbs)	2.245
Unit Carton Dimensions (H x W x L) in	10.06 x 4 x 6.56 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED; Green Energy
California Proposition 65	Lead
RoHS Certification	N/A

ACCESSORIES



156T1978AMX
1 Set of ON/OFF Trippers for T100, T7000, and WH40



156T1978A
Extra/replacement trippers 1 ON and 2 OFF



124T2411A
Insulator for Mechanical Time Switches - 10 Pack



156T1957A
Skipper Screws (3 per package)



22T338GR
Mounting Bracket for Intermatic Standardized Timer Mechanisms



6T1396
Cover, Beige plastic