

Mechanical Time Switch -

Item T101RMX



PRODUCT DESCRIPTION

The T100 Series Mechanical Time Switch has proven it can stand the test of time. These dependable time switches can handle electrical loads up to 40 A per pole and allow for up to 12 ON/OFF operations per day. A manual override switch provides added convenience.

FEATURES

- ▶ Direct 24-hour control of most loads
- ▶ Up to 12 ON/OFF operations each day with minimum ON/OFF times of one hour
- ▶ Manual override
- ▶ One ON and one OFF tripper included
- ▶ Can be installed in most Intermatic enclosures

APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	T101RMX
UPC Code	078275000056
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	1 hour
Skipper Wheel	Not Included
Operation Mode	24 hour
Has Manual Override	Yes
Application Compatibilities	LED; HID
On Events	12
Off Events	12
Total Events	24
Mechanical Specifications	
Enclosure Type	Indoor/outdoor type 3R metal
Number of Trippers Included	1 ON/1 OFF
Dimensions	
Product Dimensions (H x W x D) in	10.125 x 6.5 x 3.625 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"



Load Ratings	
Tungsten Range(s)	40 A, 120 VAC, 60 Hz
Inductive	40 A, 120 VAC, 60 Hz
Electronic Ballast Load Ratings NO Ranges	16 A, 120 VAC
Resistive Load Ratings Ranges	40 A, 120 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120 VAC, 60 Hz
Pilot Duty Load Ratings Ranges	1000 VA, 120 VAC, 60 Hz
Motor Load Ratings Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz

Electrical Specifications	
Wiring Option	Terminals
Input Voltage Range(s)	120 VAC, 60 Hz
Number of Circuits	1
Switch Type	SPST
Maximum Power Consumption (W)	3 W
Hz	60

Packaging	
Shipping Weight (lbs)	3.401
Unit Carton Dimensions (H x W x L) in	10 x 4 x 6.5 in

Environmental Specifications	
Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)

Standards and Certifications	
Other Certifications and Compatibilities	LED; NOM
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



124T1948
Insulator for Single-Pole Time Switch (T101, T102, T171, T172)



156T1957A
Skipper Screws (3 per package)



22T338GR
Mounting Bracket for Intermatic Standardized Timer Mechanisms