

Irrigation Timer -

Item T8845PV



PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

FEATURES

- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Provides for every other day operation
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure

APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Greenhouse Misting Control
- ▶ Landscape Water Control

TECHNICAL DATA

General

Model Number	T8845PV
UPC Code	078275700741
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Control Specifications

Minimum ON/OFF Times	12 min
Maximum ON/OFF Times	20 hours, 45 minutes
Trippler Actuating Time	12 min
Mechanism Type	Analog/Mechanical
On Events	60
Off Events	60
Total Events	120

Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R plastic
Number of Trippers Included	12

Dimensions

Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
-----------------------------------	-----------------

Material Specifications

Color	Gray
-------	------

Load Ratings

Clock Motor Voltage	110/125 VAC, 60 Hz
Motor Load Ratings Ranges	24 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s)	24 VAC, 60 Hz
Switch Type	SPST
Load Voltage	24 VAC, 60 Hz
Hz	60
Amperage	20 VA

Packaging

Shipping Weight (lbs)	3.243
Unit Carton Dimensions (H x W x L) in	4.25 x 7.31 x 11.75 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Lead
RoHS Certification	N/A

ACCESSORIES



156T1950A
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



133T700A
Micro Switch for T8800 and R8800 Series



156T1954A
14 Skipper Pins for R8800, and T8800 Series



T104-20



107T73
Replacement Day Wheel Pins for T8800 and R8800 Series



107T119
Tripper (Silver) for T8800 and R8800 Series (Day Skipper)



119T86A
24 VAC 20 VA Transformer, with #10 Ring Terminals



124T2097
Insulator for R8806P101C, T8805P101C, T8845PV



133T1115A
Toggle Switch for T8800 and R8800 Series

156T1950AD12
12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series



WG730-14D
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG730-14DMX
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14D
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14DMX
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



156T2978A
Package Accessory Trippers



6T1339
Cover, Gray plastic



119T85
Transformer - 24 V, 20 VA for
T8845PV



WG736-14D
480 V, 60 Hz Motor for T1900, T8800,
R8800 Series