

In-Wall Timer -

Item EI210WMX



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from 10 minutes to 1 hour
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General	
Model Number	EI210WMX
UPC Code	078275095236
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Time Presets	10 min; 20 min; 30 min; 60 min
Operation Mode	Countdown
Countdown Time	60 min
Hold Mode Included	Yes
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1
Mechanical Specifications	
Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
Material Specifications	
Color	White



Load Ratings	
Resistive Heater	15 A, 1800 W
Tungsten (Incandescent) Range(s)	1000 W
Electronic Ballast LED	500 VA
Motor Load Ratings Ranges	1/4 HP
Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Hz	60
Amperage	15 A
Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C
Packaging	
Shipping Weight (lbs)	0.351
Unit Carton Dimensions (H x W x D) in	6.131 x 2.131 x 3.001 in
Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A