

## Photocontrol - Stem and Swivel Mount Thermal Photocontrol, 120V

Item K4721D89



### PRODUCT DESCRIPTION

Intermatic's outdoor swivel mount light control is designed for residential or commercial applications and is rated to a maximum of 900 watts. Ideal for the exterior, landscape, parking lot, and pedestrian pathway lighting. It is equipped with ½"-14 NPSM threaded stem and fits standard outlet boxes and wall packs with 6" wire leads. Compatible with incandescent, fluorescent, and HID bulbs.

### FEATURES

- ▶ Mechanical bimetal switch with cadmium sulfide photocell
- ▶ 2-Year limited warranty
- ▶ Delay feature prevents unwanted OFF switching
- ▶ Integrated swivel for easy adjustments
- ▶ 6" wire leads



### TECHNICAL DATA

General	
Model Number	K4721D89
Description	Stem and Swivel Mount Thermal Photocontrol, 120V
UPC Code	078275151291
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	2-Year limited
Control Specifications	
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Photocontrol Type	Thermal
Application Compatibilities	Incandescent; Fluorescent; HID
Photocontrol Style	Stem and Swivel Mount
Photocontrol Sensor Location	Top
Dimensions	
Product Height (in)	4.33
Product Height (mm)	110
Product Width (in)	1.26
Product Width (mm)	32
Wire Lead Length (in)	6
Wire Lead Length (mm)	150
Wire Size Max	#16 AWG
Material Specifications	
Color	Black
Housing Material	Polycarbonate

**Load Ratings**

Tungsten Range(s)	900 W
Magnetic Ballast (NO) Range(s)	1100 VA

**Electrical Specifications**

Wiring Option	Wire leads
Input Voltage Range(s)	120 VAC, 50/60 Hz
Hz	50/60

**Packaging**

Shipping Weight (lbs)	0.18
Unit Carton Dimensions (H x W x D) in	4 x 3 x 1.8 in

**Operating Specifications**

Expected Lifetime (Years)	3
Expected Lifetime (Operations)	3650

**Environmental Specifications**

Temperature (operation)	-40 °F to 158 °F / (-40 °C to 70 °C)
Usage Environments	Outdoor

**Standards and Certifications**

UL Certification	cULus
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	Lead; DEHP
RoHS Certification	Y