

Mechanical Time Switch -

Item T7401B



PRODUCT DESCRIPTION

These 7-Day Mechanical Time Switches offer the capability of having a different schedule for each day of the week. They can handle up to 40 A of electrical loads per circuit and have separate terminals for powering the clock motor. These time switches can handle up to four loads per clock, providing a single control for easier installation. Each time switch comes with 7 ON and 7 OFF trippers, allowing for at least one ON/OFF operation each day.

FEATURES

- ▶ Different ON/OFF programs each day of the week
- ▶ True 7-day load control with minimum ON/OFF time of 3 1/2 hours
- ▶ Separate clock motor terminals for switching loads not on line voltage
- ▶ Carry-over automatically rewinds when power resumes
- ▶ Minimum of 16-hour carry-over for maintaining preset schedules during power failures
- ▶ Available with Type 1 rated indoor metal enclosure in a gray finish with a separate grounding terminal

APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control

TECHNICAL DATA

General	
Model Number	T7401B
UPC Code	078275461017
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	3.5 hours
Skipper Wheel	Not Included
Operation Mode	7 day
Has Manual Override	Yes
Application Compatibilities	LED; HID
On Events	24
Off Events	24
Total Events	48
Mechanical Specifications	
Enclosure Type	Indoor type 1 metal
Number of Trippers Included	14
Dimensions	
Product Dimensions (H x W x D) in	13.125 x 9 x 3.75 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG

Material Specifications

Color	Gray
-------	------

Load Ratings

Motor Single Phase Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz
Motor Three Phase Ranges	7 1/2 HP, 28 FLA @ 208 VAC, 60 Hz; 10 HP, 28 FLA @ 240 VAC, 60 Hz
Tungsten Range(s)	40 A, 120-277 VAC, 60 Hz
Inductive	40 A, 120 VAC, 60 Hz; 40 A, 208 VAC, 60 Hz; 40 A, 240 VAC, 60 Hz; 40 A, 277 VAC, 60 Hz
Electronic Ballast Load Ratings NO Ranges	16 A, 277 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120-277 VAC, 60 Hz
Pilot Duty Load Ratings Ranges	1000 VA, 120-277 VAC, Per Pole, 60 Hz

Electrical Specifications

Wiring Option	Terminals
Input Voltage Range(s)	120 VAC, 60 Hz
Number of Circuits	4
Switch Type	4-SPST
Maximum Power Consumption (W)	3 W
Hz	60
Amperage	40 A

Packaging

Shipping Weight (lbs)	9.04
Unit Carton Dimensions (H x W x L) in	9.31 x 4.13 x 12.63 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED; Green Energy
UL File Number	UL917
California Proposition 65	Lead
RoHS Certification	N/A

ACCESSORIES



156T2548A
7 Sets of ON/OFF Trippers for T7400 and T7800 Series



156T3225A
Trippers (2) Sets (ON/OFF) for T7000, WH Series (With ON/OFF Markings)



WG1600-11
Motor-125 V, 60 Hz w/Gear Cover