

## Plug-In Timer - Plug Module, J style plug with enhanced child protection, 10 A - PM JC

Item 162500042



### PRODUCT DESCRIPTION

Type J Modular plug with enhanced contact protection for use with the PT series of plug timers.

### FEATURES

- ▶ J style plug
- ▶ Child-proof lock
- ▶ Modular plug design

### TECHNICAL DATA

#### General

|                                |  |
|--------------------------------|--|
| Model Number                   | 162500042  |
| Description                    | Plug Module, J style plug with enhanced child protection, 10 A - PM JC |
| UPC Code                       | 999999999993   |
| Country of Origin (Intermatic) | MEXICO   |
| Warranty Period                | 1-Year limited   |
| TARIC HS Code                  | 8536.69.90.99  |

#### Mechanical Specifications

|                     |             |
|---------------------|-------------|
| Number of Plugs     | 1           |
| Plug Configurations | Plug Type J |

#### Dimensions

|                                   |                  |
|-----------------------------------|------------------|
| Product Dimensions (H x W x D) mm | 57 x 41.5 x mm   |
| Product Dimensions (H x W x D) in | 2.24 x 1.63 x in |

#### Material Specifications

|                  |   |
|------------------|---|
| Color            | Light Gray  |
| Housing Material | Thermoplastics, self-extinguishing & high-temperature resistant |

#### Electrical Specifications

|                           |             |
|---------------------------|-------------|
| Input Voltage Range(s)    | 230 VAC     |
| Input Voltage Frequencies | 50 or 60 Hz |

#### Packaging

|                                       |                          |
|---------------------------------------|--------------------------|
| Shipping Weight (kg)                  | 0.088                    |
| Shipping Weight (lbs)                 | 0.194                    |
| Product Weight (kg)                   | 0.08                     |
| Product Weight (lbs)                  | 0.176                    |
| Unit Carton Dimensions (H x W x D) in | 2.145 x 1.715 x 3.022 in |

|                  |      |
|------------------|------|
| Units Per Pallet | 4608 |
|------------------|------|

**Environmental Specifications**

|                         |                           |
|-------------------------|---------------------------|
| Temperature (operation) | -10 - 55 °C / 14 - 131 °F |
|-------------------------|---------------------------|

|                    |        |
|--------------------|--------|
| Usage Environments | Indoor |
|--------------------|--------|

**Standards and Certifications**

|  |     |
|--|-----|
| Other Certifications and Compatibilities | TUV |
|--|-----|

|                          |   |
|--------------------------|---|
| Standards and Guidelines | EN 60730-1, Mode of operation and additional properties: Type 1.B |
|--------------------------|---|

|                           |      |
|---------------------------|------|
| California Proposition 65 | None |
|---------------------------|------|

|                    |   |
|--------------------|---|
| RoHS Certification | Y |
|--------------------|---|