

Cycle Timer - Percentage Cycle Time Switch

Item CT2000



PRODUCT DESCRIPTION

The CT2000 Percentage Cycle Time Switch is a field adjustable timer, offering true flexibility for repetitive cycle times via an upfront control button. The timer provides repetitive cycling for short-cycle applications. The timer enclosure includes two slotted mounting holes on 5" centers and a ½" knockout for conduit connection.

FEATURES

- Provides 8 field-selectable cycle durations of 30 seconds, 1, 3, 5, 10, 30 minutes and 1 or 4 hours
- Front cover button enables true flexibility for repetitive cycle times
- Temporary and permanent manual overrides
- 30 separate positions enable precise percentage ON time selection
- User settings stored in non-volatile memory
- No DIP switches to program cycle time
- Type 3R indoor/outdoor aluminum enclosure

APPLICATIONS

- Agriculture Feeders
- Greenhouse Misting Control

TECHNICAL DATA

General	
Model Number	CT2000
Description	Percentage Cycle Time Switch
UPC Code	078275124363
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Cycle Duration	30 sec; 1 min; 3 min; 5 min; 10 min; 30 min; 1-Hour; 4 hours
Mechanical Specifications	
Enclosure Type	Outdoor type 3R metal
Dimensions	
Product Dimensions (H x W x D) in	6.625 x 3.5 x 3.313 in
Material Specifications	
Color	Gray
Load Ratings	
Tungsten Incandescent	5 A, 240 VAC, 60 Hz
Motor Load Ratings Ranges	1 HP, 120 VAC; 2 HP, 240 VAC, 60 Hz
Electrical Specifications	
Wiring Option	Wire leads



Switch Type	SPST
-------------	------

Packaging

Shipping Weight (lbs)	1.397
Unit Carton Dimensions (H x W x L) in	4.06 x 4 x 7.38 in

Environmental Specifications

Temperature (operation)	-14 °F to 140 °F / (-10 °C to 60 °C)
-------------------------	--------------------------------------

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A