

## Electronic Timer Control - Astronomic 365-Day 4-Circuit Electronic Control, 120-277 VAC, 50/60 Hz, 4-SPDT/2-DPDT, Outdoor Metal Enclosure, Ethernet Included

Item ET90415CR



### PRODUCT DESCRIPTION

The ET90000 Series combines powerful and intuitive scheduling with truly maintenance-free convenience and included capability of a 2 hour override. The PC App provides real-time remote control, and the USB connection and Ethernet capabilities enable in-field updates. These products can be used to help meet Title 24 requirements.

### FEATURES

- ▶ Automatic input voltage selection from 120 to 277 VAC, 50/60 Hz
- ▶ Over 2,000 events plus holiday schedules
- ▶ Allows for simple override control when paired with MS-101-WH Momentary Switch (sold separately)
- ▶ Advanced scheduling including relative events, such as fourth Thursday of November or first week of year
- ▶ 30 A rated contacts
- ▶ 100-hour supercapacitor eliminates the need for batteries
- ▶ USB connection for uploading, downloading and transferring programs
- ▶ Easy-to-follow on-screen menus for programming to-the-minute accuracy
- ▶ Non-volatile memory protects programming indefinitely
- ▶ Firmware can be upgraded in-field via USB or Ethernet
- ▶ Internally expandable, in 4-circuit increments, up to 16-circuits for 4, 8, and 12-circuit models

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

### TECHNICAL DATA

General	
Model Number	ET90415CR
Description	Astronomic 365-Day 4-Circuit Electronic Control, 120-277 VAC, 50/60 Hz, 4-SPDT/2-DPDT, Outdoor Metal Enclosure, Ethernet Included
UPC Code	078275124912
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	3-Year limited
Control Specifications	
Minimum ON/OFF Times	1 Sec
Minimum Pulse Time	1 sec
Maximum Pulse Time	23 hours, 59 minutes
Maximum ON/OFF Times	365 days
Operation Features	Astronomic; Holiday
Operation Mode	365 day
Data Transfer Options	Ethernet Optional/USB
Daylight Savings Adjustment	Automatic
Backup Restoration Time	30 Minutes

Backup Type	Supercapacitor
Backup Protection Time	100 Hour
On Events	2000
Off Events	2000
Total Events	2000

### Mechanical Specifications

Enclosure Type	Outdoor type 3R metal
----------------	-----------------------

### Dimensions

Product Dimensions (H x W x D) in	17.9 x 12.7 x 5.4 in
-----------------------------------	----------------------

### Material Specifications

Color	Gray
-------	------

### Communication Method

Has WiFi	No
----------	----

### Load Ratings

Tungsten (NO) Load Ratings	5 A, 12 VAC, 50 Hz; 5 A, 24 VAC, 50 Hz; 5 A, 50 VAC, 50 Hz; 5 A, 110 VAC, 50 Hz; 5 A, 115 VAC, 50 Hz; 5 A, 120 VAC, 50 Hz; 5 A, 12 VAC, 60 Hz; 5 A, 24 VAC, 60 Hz; 5 A, 50 VAC, 60 Hz; 5 A, 110 VAC, 60 Hz; 5 A, 115 VAC, 60 Hz; 5 A, 120 VAC, 60 Hz
Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC, 50/60 Hz
Magnetic Ballast (NC) Range(s)	3 A, 120-277 VAC, 50/60 Hz
Resistive (NO) Range(s)	20 A, 28VDC; 30 A, 12-240 VAC
Resistive (NC) Range(s)	10 A, 28 VDC; 10 A, 12-240 VAC
Pilot Duty (NO) Range(s)	470 VA, 120-240 VAC, 50/60 Hz
Pilot Duty (NC) Range(s)	275 VA, 120-240 VAC, 50/60 Hz
General Purpose (NC) Range(s)	10 A, 12-240 VAC, 50/60 Hz
General Purpose (NO) Range(s)	30 A, 12-240 VAC, 50/60 Hz
Electronic Ballast Load Ratings NO Ranges	8 A, 120-277 VAC, 50/60 Hz
Tungsten (NO) Range(s)	5 A, 12-120 VAC, 50/60 Hz
Motor Load Ratings NC Ranges	1/4 HP, 120 VAC, 50/60 Hz; 1/2 HP, 240 VAC, 50/60 Hz
Motor Load Ratings NO Ranges	1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC, 50/60 Hz

### Electrical Specifications

Voltage Selection Type	Auto-Voltage
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Number of Circuits	4
Switch Type	4xSPDT; 2xDPDT
Maximum Power Consumption (W)	50 W
Electronic Series	ET90000 Series
Hz	50/60
Amperage	30 A

### Packaging

Shipping Weight (lbs)	20.158
Unit Carton Dimensions (H x W x L) in	9 x 17.25 x 22.625 in

#### Environmental Specifications

Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)
-------------------------	--------------------------------------

#### Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	Title 20; Green Energy +
California Proposition 65	Lead
RoHS Certification	N/A

---

## ACCESSORIES



ET-NF  
RC Snubber Noise Filter 24-277 VAC for Electronic Controls