

Occupancy Sensor - Commercial Grade In-Wall 0-10 V Dimming PIR Occupancy/Vacancy Sensor, White

Item IOS-DOV-D-WH



PRODUCT DESCRIPTION

Intermatic's IOS-DOV-D-WH PIR technology 0-10 V dimming occupancy sensor can turn lights ON and OFF based on occupancy and allow the user to increase or decrease the lighting level.

FEATURES

- ▶ Passive Infrared (PIR) sensing for presence detection
- ▶ Coverage: 180°, up to 35 ft PIR
- ▶ Adjustable time delay
- ▶ Adjustable initial on light level
- ▶ Adjustable low trim level
- ▶ Adjustable high trim level

APPLICATIONS

- ▶ Indoor Sensing Control

TECHNICAL DATA

General	
Model Number	IOS-DOV-D-WH
Description	Commercial Grade In-Wall 0-10 V Dimming PIR Occupancy/Vacancy Sensor, White
UPC Code	078275154001
Brand	Intermatic
Warranty Period	5-Year limited
Country of Origin (Intermatic)	TAIWAN

Control Specifications	
Sensor Switch Type	Occupancy; Vacancy
Sensor Technology	0 -10 Volt Dimming; PIR (Passive Infrared); Zero-crossing
Has Walk-Through Detection	Yes
PIR Coverage Area (sq ft)	1120
Application Compatibilities	LED; Tungsten; Standard Ballast
Adjustable Ambient Light Level Detection	Auto-detecting
Adjustable Time Delay	30 sec to 30 min
Adjustable Sensitivity Settings	PIR - 60%-100%, Ultrasonic - 20%-100%

Mechanical Specifications	
PIR Coverage Pattern (degrees)	180
Mount Type	In-Wall

Dimensions	
Product Height (in)	4.625
Product Height (mm)	117.475
Product Width (in)	3
Product Width (mm)	76.2
Product Depth (in)	2.19

Product Depth (mm)	55.626
--------------------	--------

Material Specifications

Color	White
Includes Wall Plate	Yes
Finish	Gloss

Load Ratings

Electronic Ballast LED	600 VA, 120 VAC; 1385 VA, 277 VAC
Tungsten Range(s)	1000 W, 120 VAC; 1385 W, 277 VAC
Motor Load Ratings Ranges	1/6 HP, 120/240 VAC
Magnetic Ballast (NO) Range(s)	660 VA, 120 VAC; 1100 VA, 220 VAC; 1520 VA, 277 VAC
General Purpose (NO) Range(s)	12 A

Electrical Specifications

Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Occupancy Sensor Power Type	Line Voltage
Number of Circuits	1
Neutral Connection Required	Yes
Watts	1000; 1385
Hz	50/60
Amperage	10 A

Packaging

Shipping Weight (lbs)	0.307
Shipping Weight (kg)	0.139
Unit Carton Dimensions (H x W x L) in	4.625 x 3 x 2.19 in
Product Weight (lbs)	0.37

Environmental Specifications

Temperature (operation)	32 - 131°F / 0 - 55°C
-------------------------	-----------------------

Standards and Certifications

Other Certifications and Compatibilities	Green Energy +
California Proposition 65	None
RoHS Certification	N/A