

GR_Analog Time Switches - Electromechanical Quartz clock, 24-Hour, 230 VAC, 50/60 Hz / 115 VDC, DIN Mount Timer Module with Battery Backup and Manual Override, 30 minute Intervals, 16 A, SPDT - THE 211Mini 133

Item 020300031



PRODUCT DESCRIPTION

The analogue DIN rail time switches from Intermatic allows switching commands in both daily and weekly programs as well as in the 1-hour program. The products are mostly equipped with motion work, thus setting the time - especially in the weekly version - is much easier. Time and switching times can be checked at a glance, resulting in versatile application possibilities, such as passage way lighting in underpasses, showcase lighting in boutiques or control of pumps in fountains.

FEATURES

- ▶ Captive tripper levers with 30 minute intervals
- ▶ 72 hour carryover in event of power loss
- ▶ Quartz drive
- ▶ Compact size

APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Air Movement & Ventilation
- ▶ Greenhouse Misting Control
- ▶ Landscape Lighting
- ▶ Landscape Water Control
- ▶ Machinery & Pump Controls
- ▶ Outdoor Lighting Control
- ▶ Outdoor Water Fountains
- ▶ Pool Pump
- ▶ Septic Treatment
- ▶ Timing/Scheduling ON/OFF

TECHNICAL DATA

General

Model Number	020300031
Description	Electromechanical Quartz clock, 24-Hour, 230 VAC, 50/60 Hz / 115 VDC, DIN Mount Timer Module with Battery Backup and Manual Override, 30 minute Intervals, 16 A, SPDT - THE 211Mini 133
UPC Code	999999999993
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications

Clock Drive Type	Quartz
Backup Protection Time	72 Hours
Mechanism Type	Analog/Mechanical

Dimensions

Product Dimensions (H x W x D) mm	90 x 17.5 x 60 mm
Product Dimensions (H x W x D) in	3.54 x 0.688 x 2.36 in

Material Specifications

Color Gray

Electrical Specifications

Input Voltage Range(s)	230 VAC, 130 VDC
Accuracy	± 1,5 Second /Day at 20°C
Current Output	Changeover, Potential-free
Input Voltage Frequencies	50-60 Hz

Display and Format

Shortest switching time	ON/OFF 30 minutes
-------------------------	-------------------

Packaging

Shipping Weight (kg)	0.1
Shipping Weight (lbs)	0.221
Product Weight (kg)	0.11
Product Weight (lbs)	0.242
Unit Carton Dimensions (H x W x D) in	0.704 x 2.564 x 3.547 in

Operating Specifications

Channels	1
Program	Daily Program (ON/OFF)

Environmental Specifications

Temperature (operation)	-20 - 55 °C / -4 - 131 °F
-------------------------	---------------------------

Standards and Certifications

Other Certifications and Compatibilities	CE; REACH
California Proposition 65	None
RoHS Certification	Y