


In-Wall Timer - Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, With Hold, White

Item FD12HHW



PRODUCT DESCRIPTION

The FD Series Decorator Countdown Timers are designed to replace any standard or decorator style wall switch, single- or multi-gang. These mechanical timers do not require electricity to operate. They automatically limit the ON times for fans, lighting, motors, heaters and other energy consuming loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

FEATURES

- ▶ 12-Hour timer with hold
- ▶ SPST (Single-Pole Single-Throw)
- ▶ No electricity required to operate
- ▶ Replaces any standard or decorator single- or multi-gang wall switch
- ▶ Automatically limits ON time for energy consuming loads
- ▶ Quick and easy installation
- ▶ Time-saving up front terminal connection with teeter-type terminals
- ▶ Breaks circuit at end of timing cycle
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ No neutral connection is required

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control
- ▶ Motor Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General

| | |
|--------------------------------|---|
| Model Number | FD12HHW |
| Description | Spring Wound Countdown Timer, Decorator Style, 125-277 VAC, 50/60 Hz, SPST, 12 Hour Max, With Hold, White |
| UPC Code | 078275185715 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | TUNISIA |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|-----------------------------|-------------------------------------|
| Operation Mode | Countdown |
| Countdown Time | 12 hrs |
| Hold Mode Included | Yes |
| Mechanism Type | Analog/Mechanical |
| Application Compatibilities | Incandescent; Fluorescent; CFL; LED |

Mechanical Specifications

| | |
|---------------------------|-------------------------|
| Wall Plate Configurations | Single-Gang; Multi-Gang |
|---------------------------|-------------------------|

Dimensions

| | |
|-----------------------------------|------------------------|
| Product Dimensions (H x W x D) in | 4.125 x 1.75 x 1.25 in |
|-----------------------------------|------------------------|

Material Specifications

| | |
|---------------------|-------|
| Color | White |
| Includes Wall Plate | No |

Load Ratings

| | |
|---------------------------|---|
| Resistive Heater | 20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC |
| Motor Load Ratings Ranges | 1 HP, 125 VAC; 2 HP, 250 VAC |

Electrical Specifications

| | |
|-----------------------------|-----------------------|
| Input Voltage Range(s) | 125-277 VAC, 50/60 Hz |
| Wiring Configurations | Single |
| Switch Type | SPST |
| Neutral Connection Required | No |
| Hz | 50/60 |

Environmental Specifications

| | |
|-------------------------|-------------------------|
| Temperature (operation) | 40 - 120 °F / 4 - 49 °C |
|-------------------------|-------------------------|

Packaging

| | |
|---------------------------------------|-----------------------|
| Shipping Weight (lbs) | 0.299 |
| Unit Carton Dimensions (H x W x D) in | 4.63 x 2.13 x 2.88 in |

Standards and Certifications

| | |
|--|--------------|
| UL Certification | RU |
| CSA Certification | cCSAus |
| Other Certifications and Compatibilities | Green Energy |
| California Proposition 65 | DEHP |
| RoHS Certification | N/A |

ACCESSORIES



148FD5062
Plate for 12-Hr with HOLD, White
(FD12HHW)



146--00045
Knob-Wall Switch FD Series - Ivory



146--00046
Knob-Wall Switch FD Series - White



146--00047
Knob-Wall Switch FD Series - Almond



146MT416A
Knob-Wall Switch FD Series - Black