

In-Wall Timer -

Item EI210MX



PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from 10 minutes to 1 hour
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General

| | |
|--------------------------------|----------------|
| Model Number | EI210MX |
| UPC Code | 078275095229 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CHINA |
| Warranty Period | 1-Year limited |

Control Specifications

| | |
|-----------------------------|-------------------------------------|
| Time Presets | 10 min; 20 min; 30 min; 60 min |
| Operation Mode | Countdown |
| Countdown Time | 60 min |
| Hold Mode Included | Yes |
| Mechanism Type | Digital/Electrical |
| Application Compatibilities | Incandescent; Fluorescent; CFL; LED |
| On Events | 1 |
| Total Events | 1 |

Mechanical Specifications

| | |
|---------------------------|-------------|
| Wall Plate Configurations | Single-Gang |
|---------------------------|-------------|

Dimensions

| | |
|-----------------------------------|--------------------------|
| Product Dimensions (H x W x D) in | 4.125 x 1.688 x 1.438 in |
|-----------------------------------|--------------------------|

Material Specifications

| | |
|-------|-------|
| Color | Ivory |
|-------|-------|

Load Ratings

| | |
|---------------------------|--------------|
| Resistive Heater | 15 A, 1800 W |
| Electronic Ballast LED | 500 VA |
| Motor Load Ratings Ranges | 1/4 HP |

Electrical Specifications

| | |
|-----------------------------|----------------|
| Input Voltage Range(s) | 120 VAC, 60 Hz |
| Wiring Configurations | Single |
| Neutral Connection Required | Yes |
| Hz | 60 |
| Amperage | 15 A |

Environmental Specifications

| | |
|-------------------------|-------------------------|
| Temperature (operation) | 32 - 104 °F / 0 - 40 °C |
|-------------------------|-------------------------|

Packaging

| | |
|---------------------------------------|--------------------|
| Shipping Weight (lbs) | 0.35 |
| Unit Carton Dimensions (H x W x D) in | 4.88 x 3 x 2.13 in |

Standards and Certifications

| | |
|--|-------|
| UL Certification | cULus |
| Other Certifications and Compatibilities | NOM |
| California Proposition 65 | None |
| RoHS Certification | N/A |