

## In-Wall Timer -

Item EI205LA



### PRODUCT DESCRIPTION

This timer requires no programming; preset countdown times are activated by pressing a single button. Silent operation makes this timer ideal for applications where the noise of mechanical countdown timers is of concern. \*NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

### FEATURES

- ▶ No programming required
- ▶ Provides silent operation in time ranges from five minutes to 1 hour
- ▶ Single-button time selection, with some models having a HOLD mode, for continuous ON operation
- ▶ Replaces single-pole switches in a variety of applications
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ For use with decorator-style wall plate (not included)
- ▶ Requires neutral connection

### APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

### TECHNICAL DATA

#### General

Model Number	EI205LA
UPC Code	078275108462
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

#### Control Specifications

Time Presets	5 min; 15 min; 30 min; 45 min; 1 hr
Operation Mode	Countdown
Countdown Time	1 hr
Hold Mode Included	No
Mechanism Type	Digital/Electrical
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
On Events	1
Total Events	1

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

#### Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.688 x 1.438 in
-----------------------------------	--------------------------

#### Material Specifications

Color	Light Almond
-------	--------------

**Load Ratings**

Resistive Heater	15 A, 1800 W
Electronic Ballast LED	500 VA
Motor Load Ratings Ranges	1/4 HP

**Electrical Specifications**

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Hz	60
Amperage	15 A

**Environmental Specifications**

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

**Packaging**

Shipping Weight (lbs)	0.271
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

**Standards and Certifications**

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	Y