

In-Wall Timer - Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, Ivory, Mexico Sales Only

Item EI400CMX



PRODUCT DESCRIPTION

Offering a programmable countdown time between one second and 24 hours, this versatile timer can handle any application, regardless of load type. No neutral connection is required. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ Programmable countdown time interval from one second to 24 hours
- ▶ Settings stored in non-volatile memory
- ▶ Optional audible and/or visual warning of impending load switch OFF
- ▶ Lockable settings help avoid unintended changes
- ▶ Single-pole or 3-way switch compatible installation
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ Isolated switch allows timer to be used with any load type including AC and DC loads
- ▶ Replaceable CR2 lithium battery provides up to three years of operation
- ▶ No neutral wire connection enables easy retrofitting and quicker installation
- ▶ 24-hour programming allows for continuous operation

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation

TECHNICAL DATA

General

Model Number	EI400CMX
Description	Electronic Countdown Timer, Programmable, 120-277 VAC, 50/60 Hz, 1 Second to 24 Hours, Ivory, Mexico Sales Only
UPC Code	078275101371
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	5-Year limited

Control Specifications

Operation Mode	Countdown
Countdown Time	1 sec; 24 hrs
Mechanism Type	Digital/Electrical
Backup Type	Battery
Backup Protection Time	3 Years
Battery Type	CR2 Lithium
Battery Service Type	Replaceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.188 in
-----------------------------------	-------------------------

Material Specifications

Color	Ivory
-------	-------

Load Ratings

Resistive Heater	20 A, 2400-5540 W, 120-277 VAC
DC Loads	4 A, 12 VDC; 2 A, 28 VDC
Motor Load Ratings Ranges	1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC, 50/60 Hz

Electrical Specifications

Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Wiring Configurations	Single; 3-Way
Hz	50/60

Environmental Specifications

Temperature (operation)	32 - 122 °F / 0 - 50 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.399
Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A