

In-Wall Timer -

Item EJ600A



PRODUCT DESCRIPTION

12 A rated timer that provides full 7-day programming capabilities with dusk-to-dawn functionality, ideal for use with medium to low power loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

FEATURES

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Astronomic clock feature determines dawn and dusk times
- ▶ Automatic Daylight Saving Time (DST) adjustment
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Single or 3-way switch compatible installation
- ▶ Incandescent/fluorescent compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection
- ▶ Decorator switch plate not included

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	EJ600A
UPC Code	078275127883
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications

Minimum ON/OFF Times	1 min
Time Presets	Flexible
Operation Mode	24 hour
Operation Features	Astronomic; Daylight Saving Time
Mechanism Type	Digital/Electrical
Backup Type	Battery
Backup Protection Time	100 Hours
Battery Service Type	Non-Replaceable
Application Compatibilities	Incandescent; Fluorescent
Chemical Composition of the Battery Cell	Li-ion
On Events	7
Off Events	7
Total Events	14

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.438 in
-----------------------------------	-------------------------

Material Specifications

Color	Light Almond
Includes Wall Plate	No
Finish	Gloss

Load Ratings

Resistive Heater	12 A, 1440 W
Motor Load Ratings Ranges	1/2 HP
Incandescent Load Ratings (Single-Gang)	15 A, 120 VAC, 60 Hz
Incandescent Load Ratings (Multi-Gang)	12 A, 120 VAC, 60 Hz
Incandescent Single Gang Load Ratings Ranges	15 A, 120 VAC, 60 Hz
Incandescent Multi Gang Load Ratings Ranges	12 A, 120 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single; 3-Way
Neutral Connection Required	Yes
Hz	60
Amperage	12 A

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.35
Unit Carton Dimensions (H x W x D) in	6.13 x 2.13 x 3 in

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A