



### Dimensions

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

### Communication Method

Has WiFi	No
----------	----

### Load Ratings

Electronic Ballast LED	1 A
Magnetic Ballast (NO) Range(s)	20 A, 120-277 VAC
Resistive (NO) Range(s)	20 A, 28 VDC; 30 A, 120/240 VAC
Inductive Load Ratings NO Ranges	30 A, 120/240 VAC
Motor Load Ratings Ranges	1 HP, 120 VAC; 2 HP, 240 VAC
Motor Load Ratings NO Ranges	1 HP, 120 VAC; 2 HP, 240 VAC
Tungsten Incandescent Load Ratings NO Ranges	5 A, 120/240 VAC

### Electrical Specifications

Voltage Selection Type	Selector Switch
Wiring Option	Terminals
Input Voltage Range(s)	120-277 VAC, 50/60 Hz
Number of Circuits	2
Switch Type	2xSPST, 1xDPST or Pulse
Maximum Power Consumption (W)	6 W
Electronic Series	ET1700 Series
Hz	50/60

### Packaging

Shipping Weight (lbs)	2.851
Unit Carton Dimensions (H x W x L) in	3.131 x 5.251 x 8.001 in

### Environmental Specifications

Temperature (operation)	-40 °F to 104 °F / (-40 °C to 40 °C)
-------------------------	--------------------------------------

### Standards and Certifications

Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

---

## ACCESSORIES



ETBATT-1  
Battery Tray Door, ET Series



ET-NF  
RC Snubber Noise Filter 24-277 VAC for Electronic Controls