

## Electronic Timer Control - Astronomic 7-Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor Metal Enclosure, Mexico Sales Only

Item ET8115CMX

**NOM**

### PRODUCT DESCRIPTION

This series offers an easy way to upgrade from a basic mechanical time switch to an electronic time switch. These timers will allow for up-to-the-minute programming, battery backup for power loss, up to 28 events total, and automatic daylight saving time corrections without the need of user interaction. They come in standard 7-day astronomic versions.

### FEATURES

- ▶ Selector switch to determine input voltage between 120-277 VAC
- ▶ Up to 28 events total
- ▶ To-the-minute accuracy
- ▶ Temporary override or permanent manual override
- ▶ Automatic Daylight Saving Time adjustment
- ▶ Astronomic models enable dusk-to-dawn scheduling

### APPLICATIONS

- ▶ Outdoor Lighting Control
- ▶ Timing/Scheduling ON/OFF
- ▶ Machinery & Pump Controls

### TECHNICAL DATA

| General                        |   |
|--------------------------------|---|
| Model Number                   | ET8115CMX   |
| Description                    | Astronomic 7-Day 1-Circuit Electronic Control, 120-277 VAC, SPDT, Indoor Metal Enclosure, Mexico Sales Only |
| UPC Code                       | 078275089778  |
| Brand                          | Intermatic  |
| Country of Origin (Intermatic) | CHINA   |
| Warranty Period                | 1-Year limited  |

| Control Specifications      |                   |
|-----------------------------|-------------------|
| Minimum ON/OFF Times        | 1 min             |
| Maximum ON/OFF Times        | Indefinite        |
| Operation Features          | Astronomic        |
| Operation Mode              | 7 day             |
| Daylight Savings Adjustment | Automatic         |
| Backup Type                 | Battery           |
| Battery Type                | AAA               |
| Battery Service Type        | Field Serviceable |
| On Events                   | 14                |
| Off Events                  | 14                |
| Total Events                | 28 (+ Astronomic) |

| Mechanical Specifications |                     |
|---------------------------|---------------------|
| Enclosure Type            | Indoor type 1 metal |

| Dimensions |  |
|------------|--|
|------------|--|

Product Dimensions (H x W x D) in 7.875 x 5.125 x 3.4375 in

Wire Size Min #14 AWG

Wire Size Max #8 AWG

#### Communication Method

Has WiFi No

#### Load Ratings

Magnetic Ballast (NO) Range(s) 20 A, 120-277 VAC

Resistive (NO) Range(s) 20 A, 28 VDC; 30 A, 120/240 VAC

Inductive Load Ratings NO Ranges 30 A, 120/240 VAC

Motor Load Ratings Ranges 1 HP, 120 VAC; 2 HP, 240 VAC

Tungsten Incandescent Load Ratings NO Ranges 5 A, 120-240 VAC

#### Electrical Specifications

Voltage Selection Type Selector Switch

Wiring Option Terminals

Input Voltage Range(s) 120-277 VAC, 50/60 Hz

Number of Circuits 1

Switch Type SPDT

Maximum Power Consumption (W) 6 W

Electronic Series ET8000 Series

Hz 50/60

#### Packaging

Shipping Weight (lbs) 2.851

Unit Carton Dimensions (H x W x L) in 3.131 x 5.251 x 8.001 in

#### Environmental Specifications

Temperature (operation) -40 °F to 104 °F / (-40 °C to 40 °C)

#### Standards and Certifications

Other Certifications and Compatibilities NOM

California Proposition 65 None

---

## ACCESSORIES



ET-NF  
RC Snubber Noise Filter 24-277 VAC for Electronic Controls