

## Electromechanical Time Switch -

Item GM40AV-Q



### PRODUCT DESCRIPTION

The GM40AV Time Switch is a universal, electromechanical time switch designed for general purpose residential and commercial applications. The robust 40 A time switch automatically detects the input voltage without the use of a DIP switch or selector pins. The time switch automatically selects any voltage between 120-277 VAC. The mechanism is mounted in a compact UL Type 3R outdoor enclosure and can also be easily retrofitted into other Intermatic enclosure types. The time switch features a DPDT switching configuration standard (i.e. two normally open and two normally closed contacts).

### FEATURES

- ▶ Auto-voltage selection 120 VAC-277 VAC
- ▶ Captive trippers - trippers cannot be lost
- ▶ 40 A rating
- ▶ Self-recharging battery backup, "Q" models feature 72-hour carry-over
- ▶ Power and status LED indicators
- ▶ 24-Hour or 7-day models available
- ▶ Up to 48 ON/OFF operations per 24-hour period or 42 ON/OFF operations per week on "W" models
- ▶ DPDT switching configuration standard (2 NO and 2 NC Contacts)
- ▶ Manual three-way ON/OFF/AUTO override switch
- ▶ Easy-to-read clock face

### APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

### TECHNICAL DATA

#### General

Model Number	GM40AV-Q
UPC Code	078275140967
Brand	Domestic Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	15 min
Operation Mode	24 hour
Backup Type	72-hour Carry-over; Battery; Self-recharging
Backup Protection Time	72 Hours
Battery Service Type	Non-Replaceable
Mechanism Type	Electromechanical
Has Captive Trippers	Yes
Has Override Switch	Yes
Has Real-time Clock Face	Yes
Chemical Composition of the Battery Cell	Ni-MH
On Events	48
Off Events	48

Total Events 96

#### Mechanical Specifications

Enclosure Type Indoor/outdoor type 3R plastic  
Number of Trippers Included 96

#### Dimensions

Product Dimensions (H x W x D) in 8.875 x 6.609 x 3 in  
Wire Size Max #8 AWG

#### Material Specifications

Color Gray

#### Load Ratings

Magnetic Ballast (NO) Range(s) 30 A, 120 VAC; 20 A, 277 VAC  
Magnetic Ballast (NC) Range(s) 10 A, 277 VAC  
Resistive (NO) Range(s) 40 A, 120-277 VAC  
Resistive (NC) Range(s) 30 A, 120-277 VAC  
Pilot Duty (NO) Range(s) 300 VA, 120-240 VAC  
Pilot Duty Load Ratings Ranges 300 VA, 120-240 VAC  
Motor Load Ratings NC Ranges 1 HP, 12 FLA, 30 LRA @ 120 VAC; 2 HP, 10 FLA, 30 LRA @ 240 VAC  
Motor Load Ratings NO Ranges 1 HP, 16 FLA, 90 LRA @ 120 VAC; 2 HP, 12 FLA, 52 LRA @ 208-277 VAC  
Tungsten Load Ratings NC Ranges 2 A, 120 VAC  
Tungsten Incandescent Load Ratings NO Ranges 15 A, 120 VAC

#### Electrical Specifications

Voltage Selection Type Auto-Voltage  
Wiring Option Screw box lug  
Input Voltage Range(s) 120-277 VAC, 50/60 Hz  
Switch Type DPDT  
Electrical Life 50,000 operations at full load  
Hz 50/60

#### Packaging

Shipping Weight (lbs) 1.896  
Unit Carton Dimensions (H x W x L) in 9.125 x 3 x 6.75 in

#### Environmental Specifications

Operating Humidity 0-95% RH, Non-condensing  
Temperature (operation) -40 °F to 131 °F / (-40 °C to 55 °C)

#### Standards and Certifications

UL Certification cULus  
Other Certifications and Compatibilities Title 20; Green Energy  
UL File Number #E10694  
RU File Number #E10694  
California Proposition 65 None

RoHS Certification

N/A