

Photocontrol - Stem and Swivel Mount Thermal Photocontrol, 208-277 V

Item K4253



PRODUCT DESCRIPTION

These photocontrols are provided with a swivel arm for easy and flexible installation to standard outdoor light fixtures or electrical boxes.

FEATURES

- ▶ Mechanical bimetal switch with Cadmium Sulfide photocell
- ▶ Delay feature prevents unwanted OFF switching
- ▶ High strength, UV resistant plastic housing
- ▶ Swivel with 1/2"-14 NPSM threaded stem
- ▶ Washer gasket and locking nut included
- ▶ #18 AWG, 6" wire leads

APPLICATIONS

- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	K4253
Description	Stem and Swivel Mount Thermal Photocontrol, 208-277 V
UPC Code	078275067769
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications

Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1 to 5 fc
Activation Off	3 to 15 fc
Photocontrol Type	Thermal
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Stem and Swivel Mount
Photocontrol Sensor Location	Top

Dimensions

Product Height (in)	4
Product Height (mm)	101.6
Product Width (in)	1.375
Product Width (mm)	34.9
Product Depth (in)	1.375
Product Depth (mm)	34.9
Wire Lead Length (in)	6
Wire Lead Length (mm)	152
Wire Size Max	#18 AWG

Stem Diameter	1/2"
Stem Thread Size	1/2" - 14
Stem Thread Type	NPSM

Material Specifications

Color	Gray
Housing Material	Polycarbonate

Load Ratings

Magnetic Ballast (NO) Range(s)	8.3 A, 1700-2300 VA
Tungsten Incandescent Load Ratings NO Ranges	15 A, 3100-4150 W

Electrical Specifications

Wiring Option	Wire leads
Input Voltage Range(s)	208-277 VAC, 50/60 Hz
Switch Type	SPST
Hz	50/60

Packaging

Shipping Weight (lbs)	0.1
Unit Carton Dimensions (H x W x D) in	4.88 x 1.75 x 3 in

Operating Specifications

Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650

Environmental Specifications

Temperature (operation)	-40 °F to 140 °F / (-40 °C to 60 °C)
Usage Environments	Outdoor

Standards and Certifications

CSA Certification	CSA
Other Certifications and Compatibilities	Title 20; Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

ACCESSORIES



22LG116
Light Guard Accessory for K4100 Series, K4200 Series Thermal Photocontrols



K42-SW-A
Swivel Arm Accessory for EK4136S, K4100 Series Stem Mount Photocontrols



6LV1352
Light Shield Accessory for EK4036S, EK4436SM, K4000 Series Button Photocontrols