

Plug-In Timer -

Item HB880RMX



NOM

PRODUCT DESCRIPTION

Full feature plug-in timer provides 7-day programming in a weatherproof enclosure with astronomical clock and Daylight Saving Time (DST) adjustment in a convenient plug-in for quick and easy automation.

FEATURES

- ▶ 14 ON/OFF programmable events
- ▶ Full 7-day programming options, including astronomical clock, automatic DST adjustment and random mode
- ▶ 2 grounded receptacles with 24" cord and grounded plug
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ AA battery backup (included)
- ▶ Plugs directly into wall outlet

APPLICATIONS

- ▶ Landscape Water Control
- ▶ Outdoor Lighting Control

TECHNICAL DATA

| General | |
|--|-------------------------------------|
| Model Number | HB880RMX |
| UPC Code | 078275140134 |
| Brand | Intermatic |
| Country of Origin (Intermatic) | CHINA |
| Warranty Period | 1-Year limited |
| TARIC HS Code | 9107.00.00 |
| Control Specifications | |
| Operation Features | Astronomic |
| Operation Mode | 7 day |
| Backup Type | Battery |
| Battery Type | AA |
| Battery Service Type | Replaceable |
| Mechanism Type | Digital/Electrical |
| Application Compatibilities | Incandescent; Fluorescent; CFL; LED |
| Chemical Composition of the Battery Cell | Alkaline |
| On Events | 7 |
| Off Events | 7 |
| Total Events | 14 |
| Mechanical Specifications | |
| Number of Plugs | 2 |
| Plug Configurations | 5-15 |
| Dimensions | |
| Product Dimensions (H x W x D) in | 5.375 x 5 x 1.875 in |

Material Specifications

| | |
|-------|-------|
| Color | Black |
|-------|-------|

Load Ratings

| | |
|--|------------------------|
| Electronic Ballast Load Ratings NO Ranges | 500 VA, 120 VAC |
| Motor Load Ratings Ranges | 1/2 HP, 120 VAC, 60 Hz |
| Tungsten Incandescent Load Ratings NO Ranges | 1000 W, 120 VAC |

Electrical Specifications

| | |
|------------------------|----------------|
| Input Voltage Range(s) | 120 VAC, 60 Hz |
| Hz | 60 |

Packaging

| | |
|---------------------------------------|----------------|
| Shipping Weight (lbs) | 0.948 |
| Unit Carton Dimensions (H x W x L) in | 7 x 3 x 5.5 in |

Environmental Specifications

| | |
|--------------------|---------|
| Usage Environments | Outdoor |
|--------------------|---------|

Standards and Certifications

| | |
|--|------|
| Other Certifications and Compatibilities | NOM |
| California Proposition 65 | None |
| RoHS Certification | N/A |