


## Occupancy Sensor - Commercial Grade Low-Voltage Power Pack

Item IOS-PP24



### PRODUCT DESCRIPTION

The IOS-PP24 Power Pack supplies low voltage lighting control system. The power pack supplies low voltage power to occupancy sensors and other control devices, switching line voltage in response to signals from control devices. Wall plate not included.

### FEATURES

- ▶ Powers up to 6 Intermatic Low Voltage Sensors
- ▶ Zero-crossing technology for long life and performance
- ▶ Incandescent/Fluorescent/CFL/LED compatible
- ▶ 24 V Power Supply
- ▶ Mounts directly to standard or deep 4" junction box
- ▶ Allows for remote switch override

### APPLICATIONS

- ▶ Indoor Sensing Control

### TECHNICAL DATA

#### General

Model Number	IOS-PP24
Description	Commercial Grade Low-Voltage Power Pack
UPC Code	078275139930
Brand	Intermatic
Warranty Period	2-Year limited
Country of Origin (Intermatic)	CHINA

#### Control Specifications

Sensor Switch Type	Low-Voltage Power Pack
Sensor Technology	Zero-crossing
PIR Coverage Area (sq ft)	Depends on sensor being used
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

#### Mechanical Specifications

Maximum Mounting Height (ft)	No maximum mounting height
------------------------------	----------------------------

#### Dimensions

Product Height (in)	2.75
Product Height (mm)	70
Product Width (in)	1.938
Product Width (mm)	49
Product Depth (in)	1.625
Product Depth (mm)	41

#### Material Specifications

Color	White
Includes Wall Plate	No

**Load Ratings**

Motor Load Ratings Ranges	1 HP, 120/240 VAC
Magnetic Ballast (NO) Range(s)	20 A, 120/230/240/277 VAC
Tungsten Incandescent Load Ratings NO Ranges	15 A, 120 VAC; 5 A, 250 VAC

**Electrical Specifications**

Input Voltage Range(s)	120/230/240/250/277 VAC, 50/60 Hz
Occupancy Sensor Power Type	Low Voltage
Neutral Connection Required	Yes
Hz	50/60

**Power Connection**

Power Supply Output	150mA @ 24VDC (with relay connected)
---------------------	--------------------------------------

**Packaging**

Shipping Weight (lbs)	0.35
Shipping Weight (kg)	0.159
Unit Carton Dimensions (H x W x L) in	2.5 x 3 x 3.75 in

**Environmental Specifications**

Temperature (operation)	32 - 131°F / 0 - 55°C
-------------------------	-----------------------

**Standards and Certifications**

UL Certification	cULus
California Proposition 65	None
RoHS Certification	N/A