

Graesslin Mechanical Time Switch - 24-Hour 120V Electromechanical Flush Mount Timer Module with Battery Backup and Manual Override, 15 Minute Intervals, 21A, SPDT

Item MIL72EQTUZH-120



PRODUCT DESCRIPTION

The MIL72 series time switches are designed to be mounted inside a control panel and can accommodate surface/DIN rail or flush panel mounting. The MIL72 series is a light duty commercial time switch for 12-24 VAC/VDC, 120 or 208/240 VAC single-phase applications.

FEATURES

- ▶ 21 A SPDT switch
- ▶ Synchronous drive or quartz drive (Q Models) with self-recharging battery backup
- ▶ 72-hour carry-over battery backup on Q models
- ▶ Captive trippers with 15-minute intervals
- ▶ Available with or without override
- ▶ True clock face, easy-to-set
- ▶ Surface/DIN rail or flush mount
- ▶ Clear plastic dust cover
- ▶ Compact size

APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

TECHNICAL DATA

General	
Model Number	MIL72EQTUZH-120
Description	24-Hour 120V Electromechanical Flush Mount Timer Module with Battery Backup and Manual Override, 15 Minute Intervals, 21A, SPDT
UPC Code	078275153424
Brand	Domestic Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Maximum Cycle Time	24 hrs
Timing Interval	15 min
Clock Drive Type	Quartz
Backup Type	72-hour Carry-over; Battery; Self-recharging
Backup Protection Time	72 Hours
Battery Service Type	Non-Replaceable
Mechanism Type	Electromechanical
Has Captive Trippers	Yes
Has Override Switch	Yes
Has Real-time Clock Face	Yes
Application Compatibilities	CFL; Fluorescent; Incandescent
Chemical Composition of the Battery Cell	Ni-MH

Mechanical Specifications

Mounting Options Flush

Dimensions

Product Dimensions (H x W x D) in 2.609 x 2.828 x 1.359 in

Cut-Out Width (In) 2 5/8

Cut-Out Height (in) 2 5/8

Cut-Out Height (mm) 66

Material Specifications

Color White

Load Ratings

Motor Load Ratings Ranges 1 HP, 120 VAC, 50/60 Hz; 2 HP, 240 VAC, 50/60 Hz

Tungsten Incandescent Load Ratings NO Ranges 1350 W, 120 VAC

Electrical Specifications

Maximum Power Consumption (VA) 0.5

Wiring Option 1/4" Quick connect terminals

Switch Type SPDT

Hz 50/60

Display and Format

Shortest switching time ON/OFF 15 minutes

Packaging

Shipping Weight (lbs) 0.309

Unit Carton Dimensions (H x W x L) in 2.25 x 3.25 x 3.25 in

Environmental Specifications

Operating Humidity 0 to 95%, Non-condensing

Temperature (operation) -4 °F to 131 °F / (-20 °C to 55 °C)

Operating Temperature with Battery Backup -4° F to 131° F (-20° C to 55° C)

Standards and Certifications

UL Certification cRUus

CSA Certification cCSAus

Other Certifications and Compatibilities Green Energy

California Proposition 65 None

RoHS Certification N/A