

## Mechanical Time Switch -

Item T104-50



### PRODUCT DESCRIPTION

The T100 Series Mechanical Time Switch has proven it can stand the test of time. These dependable time switches can handle electrical loads up to 40 A per pole and allow for up to 12 ON/OFF operations per day. A manual override switch provides added convenience.

### FEATURES

- ▶ Direct 24-hour control of most loads
- ▶ Up to 12 ON/OFF operations each day with minimum ON/OFF times of one hour
- ▶ Manual override
- ▶ One ON and one OFF tripper included
- ▶ Can be installed in most Intermatic enclosures

### APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control

### TECHNICAL DATA

#### General

Model Number	T104-50
UPC Code	078275117143
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	1 hour
Skipper Wheel	Not Included
Operation Mode	24 hour
Has Manual Override	Yes
Application Compatibilities	LED; HID
On Events	12
Off Events	12
Total Events	24

#### Mechanical Specifications

Enclosure Type	Indoor type 1 metal
Number of Trippers Included	1 ON/1 OFF

#### Dimensions

Product Dimensions (H x W x D) in	7.875 x 5.125 x 3.437 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

#### Material Specifications

Color Gray

#### Load Ratings

Electronic Ballast Load Ratings NO Ranges	16 A, 120-277 VAC
Pilot Duty Load Ratings Ranges	1000 VA, 120-277 VAC, 50 Hz
Motor Load Ratings Ranges	2 HP, 24 FLA @ 120 VAC, 50 Hz; 5 HP, 28 FLA @ 240 VAC, 50 Hz
Tungsten Incandescent Load Ratings NO Ranges	40 A, 120-277 VAC

#### Electrical Specifications

Wiring Option	Terminals
Input Voltage Range(s)	208-277 VAC, 50 Hz
Number of Circuits	2
Switch Type	DPST
Maximum Power Consumption (W)	3 W
Hz	50

#### Packaging

Shipping Weight (lbs)	2.794
Unit Carton Dimensions (H x W x L) in	8.25 x 3.5 x 5.5 in

#### Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

#### Standards and Certifications

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED; Green Energy
UL File Number	UL917
California Proposition 65	Lead
RoHS Certification	N/A

**ACCESSORIES**



156T1978AMX  
1 Set of ON/OFF Trippers for T100,  
T7000, and WH40

156T1978A  
Extra/replacement trippers 1 ON and 2  
OFF

156T1978AD12  
12 Pack of 156T1978A Trippers for  
T100, T7000, and WH40



22T338GR  
Mounting Bracket for Intermatic  
Standardized Timer Mechanisms



156T1957A  
Skipper Screws (3 per package)



WG1574-10  
Motor-250 V, 50 Hz w/Leads



WG1574-10D  
MOTOR-BOXED,250V 50HZ