

Item Bundle - 100 A Load Center with T106M & T104M Mechanisms, 8-Breaker Spaces

Item T30604R



PRODUCT DESCRIPTION

Can be used as a load center only, or add mechanisms or wiring devices for complete control systems.

FEATURES

- ▶ Eight breaker spaces
- ▶ Reduces installation costs
- ▶ Eliminates the need for additional service panels
- ▶ Fits most of our hard-wired T100 mechanical and PE digital timers
- ▶ Control two-speed pumps with the T30604R
- ▶ Fully compatible with all electrical requirements for pool/spa installations
- ▶ Load center dead front has two knockouts and one on the side for switches or GFCIs
- ▶ Wiring devices may be installed in these load centers with the use of Standoffs, sold separately

APPLICATIONS

- ▶ Distribution/Control Panel
- ▶ Motor Control
- ▶ Pump Control

TECHNICAL DATA

General	
Model Number	T30604R
Description	100 A Load Center with T106M & T104M Mechanisms, 8-Breaker Spaces
UPC Code	078275098947
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Mechanical Specifications	
Number of Breaker Knockouts	8
Enclosure Type	3R Beige metal
Dimensions	
Product Dimensions (H x W x D) in	16.875 x 10.875 x 4.75 in
Knockout Dimensions Bottom	(4) 1/2" - 3/4", (3) 1/2", (2) 3/4" - 1"
Knockout Dimensions Back	(5) 1/2" - 3/4"
Knockout Dimensions Left	(1) 3/4" - 1"
Knockout Dimensions Right	(1) 1 3/4" x 2 3/4"
Material Specifications	
Color	Beige
Load Ratings	
Load Center Ratings	100 A, 120-208 VAC, 60 Hz; 100 A, 240 VAC, 60 Hz, Single Phase
Pilot Duty Load Ratings Ranges	1000 VA, 120-240 VAC, 60 Hz
Load Center Rating Display	100 A, 120-240 VAC, Single Phase, 60 Hz
Mechanism Supply Voltage	240/240 VAC, 60 Hz

Mechanisms	T106M & T104M
Motor Load Ratings Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz
Tungsten Incandescent Load Ratings NO Ranges	40 A, 120-240 VAC

Electrical Specifications

Number of Circuits	2
Switch Type	SPDT/DPST
Maximum Power Consumption (W)	3 W
Number of Receptacle/Switch Knockouts	2

Packaging

Shipping Weight (lbs)	14.919
Unit Carton Dimensions (H x W x L) in	6.251 x 12.001 x 17.501 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	Lead
RoHS Certification	N/A

ACCESSORIES



156T1978A
Extra/replacement trippers 1 ON and 2 Spacer-Standoff, 3" long - 4 pack
OFF



21T156A
Spacer-Standoff, 3" long - 4 pack



21T166A
Spacer-Standoff, 3" long - 2 pack



22T338GR
Mounting Bracket for Intermatic
Standardized Timer Mechanisms

22T713
Bracket Painted

8--00008A
Latch-Enclosure

124--00140A
Pool Panel Breaker Base, 8-pole

156PA13715A
1" Nonmetallic Hub Kit

24T5796-WWH
Painted Plate Filler

24T5761-WWH
Plate, Dead-Front for the T30000
Series