

## Mechanical Time Switch - 24-Hour Mechanical Time Switch, 208-277 VAC, 60Hz, DPST, Indoor/Outdoor Metal Enclosure, 1 Hour Interval

Item T104RD89



### PRODUCT DESCRIPTION

The T100 Series Mechanical Time Switch has proven it can stand the test of time. These dependable time switches can handle electrical loads up to 40 A per pole and allow for up to 12 ON/OFF operations per day. A manual override switch provides added convenience.

### FEATURES

- ▶ Direct 24-hour control of most loads
- ▶ Up to 12 ON/OFF operations each day with minimum ON/OFF times of one hour
- ▶ Manual override
- ▶ One ON and one OFF tripper included

### TECHNICAL DATA

#### General

Model Number	T104RD89
Description	24-Hour Mechanical Time Switch, 208-277 VAC, 60Hz, DPST, Indoor/Outdoor Metal Enclosure, 1 Hour Interval
UPC Code	078275000124
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	1 hour
Skipper Wheel	Not Included
Operation Mode	24 hour
Has Manual Override	Yes
Application Compatibilities	LED; HID
On Events	12
Off Events	12
Total Events	24

#### Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R metal
----------------	------------------------------

#### Dimensions

Product Dimensions (H x W x D) in	10.125 x 6.5 x 3.625 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG
Knockout Dimensions Bottom	(2) combination 1/2" - 3/4"
Knockout Dimensions Back	(1) combination 1/2" - 3/4"

**Load Ratings**

Electronic Ballast LED	16 A, 120/277 VAC
Tungsten Incandescent Load Ratings NO Ranges	40 A, 120-277 VAC

**Electrical Specifications**

Wiring Option	Terminals
Input Voltage Range(s)	208-277 VAC, 60 Hz
Number of Circuits	2
Switch Type	DPST
Maximum Power Consumption (W)	3 W
Hz	60
Amperage	20 A

**Packaging**

Shipping Weight (lbs)	3.393
Unit Carton Dimensions (H x W x L) in	4 x 7.06 x 11.5 in

**Environmental Specifications**

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

**Standards and Certifications**

UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy; LED
UL File Number	UL917
California Proposition 65	Lead

## ACCESSORIES



156T1978AMX  
1 Set of ON/OFF Trippers for T100, T7000, and WH40

156T1978A  
Extra/replacement trippers 1 ON and 2 OFF

156T1978AD12  
12 Pack of 156T1978A Trippers for T100, T7000, and WH40



22T338GR  
Mounting Bracket for Intermatic Standardized Timer Mechanisms



124T1952  
Insulator for Double-Pole Time Switch (T103, T104, T105, T173, T174, T175, T104, T106, T172, T174, T176, WH40 T176, T185, WH40)



WG1573-10DMX  
208-277 VAC, 60 Hz Motor for T102,



156T1957A  
Skipper Screws (3 per package)