

Plug-In Timer - Plug-in timer, Digital clock timer, 7-Day or 24-Hr programming, 230 VAC, 50/60 Hz, 16 A, 20 Setpoint Programs, SPDT, F style plug with enhanced child protection - PT 600 F 192

Item 161500011



PRODUCT DESCRIPTION

The PT 600 F digital plug-in time switch features 20 memory spaces and allows precise switching, even after a power failure or a clock change. Thanks to a range of programs, such as the daily program, weekly program or random switching, and with a very short switching time of only 1 minute, you can realize a wide variety of highly-flexible switching options. In addition, a manual switch enables quick manual switching on and off without affecting programming.

FEATURES

- ▶ 24-hour or 7-day applications
- ▶ 20 setpoint programs
- ▶ Three preset adjustable block programs
- ▶ Menu driven programming
- ▶ Manual override with status indicator
- ▶ Battery backup
- ▶ 1 minute switching time

APPLICATIONS

- ▶ Indoor Lighting Control

TECHNICAL DATA

General	
Model Number	161500011
Description	Plug-in timer, Digital clock timer, 7-Day or 24-Hr programming, 230 VAC, 50/60 Hz, 16 A, 20 Setpoint Programs, SPDT, F style plug with enhanced child protection - PT 600 F 192
UPC Code	999999999993
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00
Control Specifications	
Minimum ON/OFF Times	1 min
Operation Mode	24 hour; 7 day
Backup Type	Battery
Backup Protection Time	3 Years
Mechanism Type	Digital/Electrical
On Events	10
Off Events	10
Total Events	20
Mechanical Specifications	
Number of Plugs	1
Plug Configurations	Plug Type F
Dimensions	
Product Dimensions (H x W x D) mm	146 x 73 x 75 mm
Product Dimensions (H x W x D) in	5.75 x 2.87 x 2.95 in

Material Specifications	
Color	Gray
Housing Material	ABS plastic
Housing type	Surface mounted

Electrical Specifications	
Input Voltage Range(s)	230 VAC \pm 10%, 50/60 Hz
Input Voltage Frequencies	50 or 60 Hz
Hz	50/60

Packaging	
Shipping Weight (kg)	0.295
Shipping Weight (lbs)	0.65
Product Weight (kg)	0.23
Product Weight (lbs)	0.506
Unit Carton Dimensions (H x W x D) in	6.4 x 3.5 x 3.245 in

Environmental Specifications	
Temperature (operation)	-10 - 55 °C / 14 - 131 °F
Usage Environments	Indoor

Standards and Certifications	
Other Certifications and Compatibilities	REACH
Standards and Guidelines	EN 60730-1, Mode of operation and additional properties: Type 1.B
California Proposition 65	None
RoHS Certification	Y