

Graesslin Electronic Timer Control - 24-Hour or 7-Day 120-277V Electronic Surface/DIN Rail Mount Module, 15A, 14 Setpoint Programs, SPDT

Item FM1D14A-AV



PRODUCT DESCRIPTION

The FM1D14 Series is a great value electronic time-based control solution for ventilating, heating, cooling, lighting or other electrical loads in commercial and industrial applications. These one-channel time switches are programmable for 24-hour or 7-day schedules. The FM1D14 Series is intended for either panel, surface, flush or DIN rail mounting. Flush and surface/DIN rail (A & E models) are completely enclosed in a plastic housing and include a terminal cover, dust cover and subbase for installation and hard wiring.

FEATURES

- ▶ 24-Hour, 7-day or Cycle timer applications
- ▶ 14 Setpoint programs
- ▶ Easy to program
- ▶ Manual override with status indication
- ▶ Self-recharging battery with backup protection up to 2500-hours
- ▶ LCD display
- ▶ 5 Preset adjustable block programs
- ▶ A & E models come with clear dust cover

APPLICATIONS

- ▶ Refrigeration Merchandiser
- ▶ Air Movement & Ventilation
- ▶ Aeration
- ▶ Septic Treatment
- ▶ Generator Exercising

TECHNICAL DATA

General	
Model Number	FM1D14A-AV
Description	24-Hour or 7-Day 120-277V Electronic Surface/DIN Rail Mount Module, 15A, 14 Setpoint Programs, SPDT
UPC Code	078275143166
Brand	Domestic Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	1 min
Operation Mode	24 hour; 7 day; Cycle
Daylight Savings Adjustment	Manual
Backup Type	Battery
Backup Protection Time	2500 Hours
Battery Service Type	Non-Replaceable
Mechanism Type	Digital/Electrical
Has Manual Override Status Indication	Yes
Application Compatibilities	LED
Chemical Composition of the Battery Cell	Ni-MH
On Events	7
Off Events	7

Total Events 14

Mechanical Specifications

Mounting Options Surface; DIN Rail

Dimensions

Product Dimensions (H x W x D) in 4 x 2.83 x 2.06 in
 Cut-Out Width (In) 2 5/8
 Cut-Out Width (mm) 66
 Cut-Out Height (in) 2 5/8
 Cut-Out Height (mm) 66
 Wire Size Min #24 AWG
 Wire Size Max #10 AWG

Material Specifications

Color White

Load Ratings

Magnetic Ballast (NO) Range(s) 8 A, 277 VAC
 Magnetic Ballast (NC) Range(s) 8 A, 120 VAC
 Resistive (NC) Range(s) 12 A, 24 VDC
 General Purpose (NC) Range(s) 15 A, 277 VAC
 General Purpose (NO) Range(s) 15 A, 277 VAC
 Electronic Ballast Load Ratings NO Ranges 4.9 A, 120 VAC
 Motor Load Ratings NC Ranges 1/2 HP @ 120/240 VAC; 10 FLA, 60 LRA @ 250 VAC
 Motor Load Ratings NO Ranges 1/2 HP @ 120 VAC; 10 FLA, 60 LRA @ 250 VAC; 1 HP @ 250 VAC
 Tungsten Incandescent Load Ratings NO Ranges 1000 W, 120 VAC

Electrical Specifications

Maximum Power Consumption (VA) 4
 Voltage Selection Type Voltage Specific
 Wiring Option Screw terminals for #24 to #10 AWG wire (A models)
 Number of Circuits 1
 Switch Type SPDT
 Maximum Power Consumption (W) 1.4 W
 Amperage 15 A

Packaging

Shipping Weight (lbs) 0.529
 Unit Carton Dimensions (H x W x L) in 3.25 x 3.25 x 4.75 in

Operating Specifications

Expected Lifetime (Operations) 6000

Environmental Specifications

Operating Humidity 0-95% RH, Non-condensing
 Display Operating Temperature Min (°F) 5

Display Operating Temperature Min (°C)	-15
Temperature (operation)	5 °F to 131 °F / (-15 °C to 55 °C)

Standards and Certifications

UL Certification	cRUus
CSA Certification	cCSAus
Other Certifications and Compatibilities	CA Title 20; Green Energy
RU File Number	#E10694
California Proposition 65	None
RoHS Certification	Y