

## In-Wall Timer - In-Wall Astro Timer - White

Item IW600K



### PRODUCT DESCRIPTION

A 15 A rated timer that provides full 7-day programming capabilities with dusk-to-dawn functionality, ideal for use with medium to low power loads. Wall plate not included.

### FEATURES

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Astronomic clock feature determines dawn and dusk times
- ▶ Automatic Daylight Saving Time (DST) adjustment
- ▶ Single-pole switch
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Incandescent/fluorescent compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection

### TECHNICAL DATA

#### General

Model Number	IW600K
Description	In-Wall Astro Timer - White
UPC Code	078275143449
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

#### Control Specifications

Minimum ON/OFF Times	1 min
Time Presets	Flexible
Operation Mode	24 hour
Operation Features	Astronomic; Daylight Saving Time
Mechanism Type	Digital/Electrical
Backup Type	Battery
Backup Protection Time	100 Hours
Battery Service Type	Non-Replaceable
Application Compatibilities	Incandescent; Fluorescent
Chemical Composition of the Battery Cell	Ni-MH
On Events	7
Off Events	7
Total Events	14

#### Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

#### Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.438 in
-----------------------------------	-------------------------

#### Material Specifications

Color	White
Includes Wall Plate	No
Finish	Gloss

**Load Ratings**

Resistive Heater	15 A, 1875 W
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP
Tungsten Incandescent Load Ratings NO Ranges	1000 W

**Electrical Specifications**

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes
Watts	1875
Hz	60
Amperage	15 A

**Environmental Specifications**

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

**Packaging**

Shipping Weight (lbs)	0.35
Unit Carton Dimensions (H x W x D) in	6.7 x 2 x 4.875 in

**Standards and Certifications**

UL Certification	cULus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP